



BenQ DLP Projector

LU930

Feature High Light

- * Laser light source
- * 5000 ANSI Lumens High Brightness
- * Big zoom & lens shift
- * 360-degree Projection
- * Digital shrink and shift
- * Display Resolution Switch
- * LumiExpert



Display

Projection System	DLP Single 0.48" WUXGA
DMD type	DC3 DMD chip
Native Resolution	1920 x 1200 pixels, 16:10
Brightness	5,000 Lumens
Contrast Ratio*	3,000,000:1
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Laser
Light Source Life†	20,000 hrs

Optical

Throw Ratio	1.36 ~ 2.18
Zoom Ratio	1.6x
Lens Control	Manual Focus
Lens shift	Manual lens shift, V: ±60 %; H: ±23 %
Keystone Correction	2D keystone, V: ±30 degree; H: ±30 degree
Projection Offset	NA
Projection Size	30" ~ 300"

Audio

Built-in Speaker	10W x2
------------------	--------

Special Feature

Security (防盜為主)	Security Bar, Kensington anti-theft lock slot
Feature	Digital Shrink and Shift, 360° Projection, LumiExpert, LAN Control(AMX/ PJ Link/Creston), MDA/DMS Local Compatibility, FW upgrade via LAN

Smart System

OS System	N/A
ROM/RAM	N/A

Wireless

Wireless	N/A
Bluetooth	N/A

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
Horizontal Frequency	15~102KHz
Vertical Scan Rate	23 ~ 120 Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM

Power

Power Consumption(Max/Normal/Eco)	Max 475W/ Normal 415W/ Eco 325W
Standby Power Consumption	Normal < 0.5W, Network < 2W,
Power Supply	100 ~ 240V AC

Dimension and Weight

Product Dimensions (WxHxD)	416 x166 x351 mm
Product Weight	6.3 Kg

Operation Condition

Noise Level(Normal/Eco)	37/30 dB
Operating Temperature	0 ~ 40°C

Accessories

Accessories (Standard)	Power Cord (by region) Remote Control w/ Battery (RCE016) HDMI cable Warranty Card (by region) QSG
Accessories (Optional)	3D Glasses (5J39H25.002) Ceiling mount (CMG3) WDC10 WDC20 Qcast Mirror

OSD

On Screen Display Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/Japanese/ Korean/ Norwegian/ Polish/ Portuguese/
----------------------------	---

Environment Notice

* The Contrast is measure by Full On Full Off standard.

* LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

* Storage: Temperature: -20~60°C; Humidity: 10~90%RH (without condensation)



Connectivity




	Quantity		Quantity
1 HDMI (1.4a)	2	11 RCA Audio in- L/R	1
2 PC (D-sub 15pin)	1	12 IR Receiver(Front+Top)	2
3 Monitor out (D-sub 15pin,Female)	1	13 12V Trigger	1
4 Audio in(mini jack)	1	14 Kensington anti-theft lock slot	1
5 Audio out (mini jack)	1		
6 RS232 In (D-sub 9pin, male)	1		
7 LAN Port(RJ45 for Network)	1		
8 USB TypeA-2 (5V,1.5A, Service)	1		
9 Component Video in	1		
10 Composite Video in (RCA)	1		


Dimension

Dimensions

414 mm (W) x 166 mm (H) x 351 mm (D)




Ceiling/Wall mount installation diagram



BenQ ceiling mount CMG3 (5J)AM10.001
Ceiling mount screw: M4
(Max. L = 25 mm; Min. L = 20 mm)

Unit: mm

Installation



30	762	404	646	879	1144	1409	0
50	1270	673	1077	1465	1906	2348	0
60	1524	808	1292	1758	2287	2817	0
70	1778	942	1508	2051	2669	3287	0
80	2032	1077	1723	2343	3050	3756	0
90	2286	1212	1939	2636	3431	4226	0
100	2540	1346	2154	2929	3812	4696	0
110	2794	1481	2369	3222	4194	5165	0
120	3048	1615	2585	3515	4575	5635	0
130	3302	1750	2800	3808	4956	6104	0
140	3556	1885	3015	4101	5337	6574	0
150	3810	2019	3231	4394	5719	7043	0
200	5080	2692	4308	5859	7625	9391	0
250	6350	3365	5385	7323	9531	11739	0
300	7620	4039	6462	8788	11437	14087	0

*To optimize your projection quality, we suggest to do the projection within non-gray area.

