

Heylo PowerFilter 3500 – air cleaner

Air cleaner

HEYLO becomes MASTER
in proven quality

HEYLO[®]

MCS MASTER[®]
CLIMATE SOLUTIONS

During the restoration of buildings or during industrial work, noxious particles (dust, mould spores, et cetera) are released frequently which jeopardise people when they spread at the place of work or in the remaining building.

The high-performance cleaner PF 3500 makes sure that harmful substances are removed at the source immediately so that they cannot get into other parts of the building.

The high-performance cleaner PowerFilter PF 3500 is the ideal unit for air cleaning for industry as well. By connecting several hoses, the dust filter and dust extraction even at different workplaces can be carried out at the same time.



Heylo air cleaner PF 3500



Heylo air cleaner PF 3500 back



Heylo air cleaner PF 3500 open



Heylo air cleaner PF 3500 hoses



Heylo air cleaner PF 3500 wheels



Heylo air cleaner PF 3500 panel

Key features

- ✓ Connection of several hoses: flexible use at several workplaces at the same time
- ✓ Infinitely variable air flow
- ✓ 3-stage filter system
- ✓ MID energy metre (kWh)
- ✓ For tough use – also in industry
- ✓ Can be closed after use of contaminants
- ✓ Robust metal housing
- ✓ Quiet and very energy efficient operation
- ✓ Filter change indicator

- ✓ Operating hours counter
- ✓ Including 3x pre-filter G4

Various filters are accessible quickly and can be exchanged easily:

- Pre-filter - coarse dust filter of class G4 in conformity with European standard EN779
- Main filter - fine dust filter of Class F9 in conformity with European standard EN779 and dust class M in conformity with EN60335
- Main filter - suspended solids filter HEPA H14 in conformity with European standard EN1822 and dust class M in conformity with EN60335
- Main filter - activated carbon filter

Product specifications

Specifications	Units	PF 3500
Fan air flow rate max.	m³/h	3,100
Air flow with F9 filter /M-class/H14 filter/H-class	m³/h	2,795/2,420
Min. air flow by saturated filters	m³/h	1,700
Power supply	V/Hz	230/1ph/50-60
Power consumption	kW	0.48
Current consumption	A	2.5
Sound level @3m	dB(A)	0-70
Hose inlet/outlet	Ømm	205
Product size (l x w x h)	mm	710 x 460 x 1010
Weight	kg	48

Suitable for:

- ▲ Camps and field hospitals

- ▲ Commercial buildings
- ▲ Construction
- ▲ Events and festivals
- ▲ Industrial, factories and production
- ▲ Leisure and recreation
- ▲ Military and aerospace
- ▲ Rental companies
- ▲ Transport and logistics