



grandMA3 onPC 2Port Node 2k PoE

Art.-No. 4010512-1



The grandMA3 onPC 2Port Node 2k PoE is the smartest solution within MA Lighting's range of Nodes. It is cost-effective – and just as powerful as its larger models. The Node is the perfect entry-level for the grandMA3 onPC software - just connect it with a PC and control your fixtures directly. It is also the most flexible device to distribute the DMX lines in many different places in your installation. Might it be theatre, TV or house of worship, you can get your DMX in- and outputs wherever you need them.

The grandMA3 onPC 2Port Node 2k PoE comes in a 9.5" 1RU housing and is designed to synchronously output two DMX universes in any grandMA3 system. To ensure optimal performance, the Node is equipped with a high-performance processor and a 1 Gb/s Ethernet connection, guaranteeing reliable and stable Ethernet to DMX (and vice versa) conversion. It can be fully powered by PoE (Power over Ethernet) to reduce additional cabling. A wide range of accessories allows for alternative fixing methods and customization if required.

All grandMA3 onPC Nodes enable 4 096 parameters for the grandMA3 onPC software directly. To initiate a compact and cost-effective control system, simply download the grandMA3 onPC software, connect the Node, and you're ready to control your fixtures. As the grandMA3 onPC software offers the same features as the larger consoles of MA Lighting, there will be no compromises on features for your show.

Some more facts to know? All grandMA3 Nodes are remotely configurable from any grandMA3 console or onPC station within the network session. They are capable of handling MA-Net3, MA-Net2, sACN and Art-Net data. They are fully RDM compliant. A 3.9" color display on the front face allows for simple configuration and a quick status overview.



Scope of delivery

Art.-No.	Article	Quantity
4025695	MA Quick Manual for grandMA3 Nodes	1

1x powerCON TRUE1 socket (NAC3FX-W-TOP) or similar

Technical Specifications

Parameters	4 096 (HTP/LTP)
Parameters Mode2	1 024 (HTP/LTP)
Operating voltage/ Supply voltage	AC 100 - 240 V; 50/60 Hz PoE (IEEE 802.3af; 48 V DC/max. 12 W)
Power	max. 15 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	207 x 184 x 43 mm / 9 x 8 x 2 in (width x depth x height)
Net weight	2 kg / 5 lbs
Connectors	1 x powerCON TRUE1 1 x etherCON/RJ45 2 x DMX512-A Out (5pin XLR female) 1 x USB 2.0 (type A)

Article

Art.-No.	Article
4010512-1	grandMA3 onPC 2Port Node 2k PoE

Accessories

Art.-No.	Article
130281	MA 2Port Node / 4Port Node 19" rack mounting kit - blank panel
130285	MA 2Port Node 19" rack mounting kit - XLR connectors
130283	MA 2Port Node / 4Port Node 19" rack mounting kit - 2x Nodes
130284	MA 2Port / 4Port / 8Port Node rigging plate
210650	Adapter cable set for MA 2Port Node, 2x cable DMX/XLR5 to DMX (length 0.5m), 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45
210627	Adapter cable set for MA 2Port / 4Port Node, 4x cable DMX/XLR5 to DMX (length 0.5m)
210628	Adapter cable set for MA 2Port / 4Port Node, 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45

More product pictures

