



grandMA3 onPC rack-unit

Art.-No. 4023806



You are looking for a grandMA3 onPC control solution to be installed in a 19" rack? You work in a fixed installation like a theater, shopping mall, TV/streaming studio or house of worship and need a reliable backup solution for your grandMA3 lighting control system? Or you want to implement a stand-alone lighting control system for your show that runs automatically due to external triggers, for example in a theme park or for architectural lighting?

If you can tick one of these boxes, the grandMA3 onPC rack-unit is the perfect solution for you. It is a first class onPC controller in 19" format with the grandMA3 onPC software already pre-installed on a powerful computer. So you won't miss any features or software functionality compared to the grandMA3 consoles. Just connect a mouse, a keyboard and up to two external monitors and you can directly control 4 096 parameters.

The device will be shipped with Windows IoT - so we can make sure it can get a proper factory reset image if needed.

It is not only a powerful control solution, but also an optimal playback device. All relevant connections - DMX Out/Inputs, MIDI In/Out, Timecode and DC remote - are already built in for direct use. Maybe your show is triggered by agenda events and runs automatically - the grandMA3 onPC rack-unit is the perfect solution for many installation projects.

Imagine you want to create a solution for a small to medium sized installation: You can combine the grandMA3 onPC rack-unit with a grandMA3 onPC command wing and/or up to two grandMA3 onPC fader wings to control or pre-program your show. In addition, it can act as a full-fledged and reliable backup unit in your grandMA3 lighting control system.



Features

- Real-time control for 4 096 parameters - in combination with the pre-installed grandMA3 onPC software
- 2 DMX outputs, 1 DMX input
- 2 external multi-touch screens can be connected
- 1 internal multi-touch command screen
- 2 RJ45 connectors
- 6 USB connectors
- Various control interfaces

Scope of delivery

Art.-No.	Article	Quantity
4025893	MA Quick Manual for grandMA3 onPC rack-unit	1

1 x MA power cable, IEC-C plug (lockable), length 2.0 m, open end

Technical Specifications

Parameters	4 096 (HTP/LTP)
Parameters Mode2	not applicable (no Mode2)
Operating voltage/ Supply voltage	AC 100 - 240 V; 50/60 Hz
Power	max. 100 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	482 x 249 x 87 mm / 19 x 10 x 4 in (width x depth x height)
Net weight	4 kg / 9 lbs
Connectors	1 x IEC-60320 C14 cord 2 x RJ45 2 x DMX512-A Out (5pin XLR female) 1 x DMX512-A In (5pin XLR male) 1 x MIDI In (5pin DIN female) 1 x MIDI Out (5pin DIN female) 1 x Linear Timecode (3pin XLR female) 1 x Audio In (mini jack 3.5mm) 1 x Audio Out (mini jack 3.5mm) 1 x GPI General Purpose Interface (D-SUB DE9 female) for remote control 2 x DisplayPort 1.2 for external screens 4 x USB 2.0 (type A) 2 x USB 3.0 (type A)

Article

Art.-No.	Article
4023806	grandMA3 onPC rack-unit

Accessories

Art.-No.	Article
4010511	grandMA3 onPC command wing
4023575	grandMA3 onPC fader wing



More product pictures

