



APC Easy UPS, 800VA, Floor/Wall Mount, 230V, 6x IEC C13 outlets, AVR

BV800I

Call for More Information 0800 115308

- Includes: User manual

Output	
Output power capacity	450 Watts / 800VA
Max Configurable Power (Watts)	450 Watts / 800VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Unsynchronised
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(6) IEC 60320 C13
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Input Connections	IEC 60320 C14
Cord Length	1.5meters
Input voltage range for main operations	170 - 280V
Number of Power Cords	1

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Nominal Battery Voltage	12 V
Expected Battery Life (years)	3 - 5

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS, 800VA, Floor/Wall Mount, 230V, 6x IEC C13 outlets, AVR | BV800I | Downloaded on 02/12/2023 (EST)



Batteries & Runtime

Efficiency	View Efficiency Graph (Available in Technical Tab on site)
------------	--

Surge Protection and Filtering

Surge energy rating	156Joules
---------------------	-----------

Physical

Maximum Height	93MM, 9.25CM
Maximum Width	161MM, 16.05CM
Maximum Depth	305MM, 30.5CM
Net Weight	5.3KG
Shipping weight	5.6KG
Shipping Height	237MM, 23.7CM
Shipping Width	373MM, 37.3CM
Shipping Depth	143MM, 14.3CM
Color	Black
SCC Codes	10731304338342

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0 - 2032.1meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 90 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	40.0dBA
Protection Class	IP20

Conformance

Approvals	CE
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS, 800VA, Floor/Wall Mount, 230V, 6x IEC C13 outlets, AVR | BV800I | Downloaded on 02/12/2023 (EST)



Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.