



Combi Drill LXT®

DHP458RTJ

18V • 91 Nm • 0 – 2 000 min⁻¹

Rugged combi drill for heavy-duty screwdriving and drilling

A powerful drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 91 / 58 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. Two 5.0Ah batteries and a rapid charger in a Makpac case.



LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery protection	✓
No load speed	0 - 400 / 2000 min ⁻¹
Max. fastening torque Hard/Soft	91 / 58 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 6000 / 30 000 min ⁻¹
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Concrete	16 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	95 dB(A)

User benefits

- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381815024

Link to product - www.makitauk.com



Related products

Standard AC

122576-8

Stopper Pole



123257-7

Side Handle



251314-2 (2x)

Truss Head Screw M4*12, Td140D



346317-0

Belt Hook



450128-8

Battery cover, LXT®, 14,4 – 18V



452947-8

Bitholder



687329-7

Band

784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double



821550-0

Makpac case (2)



Standard MA

BL1850B

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

122576-8

Stopper Pole



251314-2

Truss Head Screw M4*12, Td140D



450128-8

Battery cover, LXT®, 14,4 – 18V



452947-8

Bitholder



763252-1

Keyless Drill Chuck

821550-0

Makpac case (2)



Other

User manual

Parts drawing