


HIDDEN IP IR CAMERA DUMMY PIR HOUSING

IV-390IP537



1/2.7" CMOS Sensor
2 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
Analytics Support

3.6mm Mega-Pixel Lens
30m IR Illumination
PoE Support
1 Way Audio (Built-In Microphone)
CVBS

Local Storage



Specifications (Based on v4.2.1)

Camera	Video	Model	I3-390IP536
		Image Sensor	1/2.7" CMOS (16:9)
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
		Analytics	Camera Tampering, Line Crossing, Sterile Area, Smart Search
	Compression	Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)
		Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF
		Multi-Stream	Main Stream: 1920x1080 / 1280x720 (1~25/30FPS) Sub-Streams D1 / CIF (1~25/30FPS)
		Bit rate	64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	10m (20 IR LED)
	Lens (Field of View)	3.7mm (78.9°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	None
	Bracket	3-Axis Wall Bracket
	Dimensions	95*69.5*58mm
	Weight(gross)	269g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket / PoE
	Analog Video Output	No
	Audio Connectivity	Built-In Microphone or 1Ch Audio input
	SD Card	Support Event recording over TF (128GB Max)
	RS485	No
	Alarm	No
Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~420mA / PoE/~4.8W
	Work Environment	-20 C ~50 C, 10%~90% Humidity

