



Xprinter®

Mobile Label Printer

XP-P441B




- LCD screen, easy to operate
- Low noise, high quality, high speed printing
- 2500mAh large capacity battery, long standby
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS emulation compatible



XP-P441B

Mobile Label Printer



Printing		XP-P441B
Resolution		203 DPI
Printing method		Direct Thermal
Max.print speed		Max. 100mm (3.937") / s
Max.print width		108 mm (4.25")
Max.print length		1778 mm (70")
Media		
Media type		Continuous, gap, black mark
Media width		40 mm ~ 112 mm
Media thickness		0.06 mm ~0.254 mm
Paper roll diameter		50 mm
Performance Features		
Processor		32-bit CPU
Memory		8MB Flash Memory/ 8MB SDRAM
Interface		Standard version: USB+Bluetooth Optional:USB+WIFI / NFC
Screen		1.3"OLED
Sensors		①Gap sensor ②Cover opening sensor ③Black mark sensor
Performance Features		
Internal fonts		8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code		Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code		PDF-417, Maxicode, DataMatrix, QR code
Rotation		0°、 90°、 180°、 270°
Emulaion		TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS
Physical Features		
Dimensions		150 mm (L) x 131 mm (W) x 64 mm (H)
Weight		0.45kg
Reliability		
Printer head life		30Km
Software		
Operation system		Windwos / Linux / Mac / Android / iOS
SDK		Windows / Android / iOS
Power supply		
Input/Output		Input: AC 100-240V,0.5A 50-60Hz ; Output: DC 5V/ 2A
Battery life		7.4V/2500mAh
Options		
Optional accessories		①Shoulder strap ②Protection bag ③Dual-slot battery charger
Environmental Conditions		
Operation environment		-10 ~ 45°C (14~113°F) , Humidity: 25 ~ 85% no condensing
Storage environment		-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

