

Product datasheet

Specifications



APC Smart-UPS RV 3000VA 230V

SRV3KI

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead Time	Usually in Stock

Main

Main Input Voltage	230 V
Product Or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	2400 W
Rated Power In Va	3000 VA
Input Connection Type	IEC 60320 C20
Output Connection Type	6 IEC 60320 C13 1 IEC 60320 C19
Cable Length	1.5 m
Number Of Cables	1
Provided Equipment	1 IEC 60320 C19 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable user manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Lead-acid battery
Battery Voltage	72 V
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	4 h
Battery Life	3...5 year(s)
Replacement Battery	APCRBCV205

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Charger Power	60 W rated
-----------------------	------------

General

Number Of Power Module Filled Slots	0
-------------------------------------	---

Number Of Power Module Free Slots	0
-----------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Black (RAL 7010)
--------	------------------

Height	33.6 cm
--------	---------

Width	19 cm
-------	-------

Depth	42.5 cm
-------	---------

Net Weight	26.8 kg
------------	---------

Mounting Location	Front
-------------------	-------

Mounting Preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Usb Compatible	Yes
----------------	-----

Mounting Position	Vertical
-------------------	----------

Input

Input Voltage Limits	110...285 V half load 160...280 V full load
----------------------	--

Network Frequency	40...70 Hz auto sensing
-------------------	-------------------------

Output

Maximum Configurable Power In Va	3000 VA
----------------------------------	---------

Maximum Configurable Power In W	2400 W
---------------------------------	--------

Output Frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Harmonic Distortion	3 %
---------------------	-----

Ups Type	Double conversion online
----------	--------------------------

Wave Type	Sine wave
-----------	-----------

Efficiency	88 % (full load)
------------	------------------

Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

Bypass Type	Internal bypass (automatic and manual)
-------------	--

Crest Factor	3 : 1
--------------	-------

Conformance

Product Certifications	CE UKCA EAC TISI
------------------------	---------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	50 dBA
Heat Dissipation	910 Btu/h
IP Degree Of Protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Free Slots	1
Control Panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge Energy Rate	600 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	46.5 cm
Package 1 Width	32.5 cm
Package 1 Length	56.5 cm
Package 1 Weight	29 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more >](#)



Energy Efficient

Resource performance

 Energy Efficient Product

Reach Regulation

[REACh Declaration](#)

Eu RoHS Directive

Compliant

[EU RoHS Declaration](#)
