

Eaton EBAB19

Catalog Number: EBAB19

Eaton Basic Rack PDU, 0U, 10U, C14 input, 2 kW, 10A, 200-240V, Outlets: (12) C13

General specifications



Product Name	Catalog Number
Eaton basic rack PDU	EBAB19
Model Code	UPC
EPDU BA 0U (C14 10A 1P)12XC13	743172065810
Product Length/Depth	Product Height
439 mm	52 mm
Product Width	Product Weight
53 mm	1.3 kg
Compliances	Certifications
CE Marked	CE
RoHS Compliant	IEC 60950-1
EAC	EN 55024:2010

Special features

Built-in IEC outlet eGrip retention, retains all standard IEC plugs

Built-in outlet P-lock system, locking mechanism with P-lock power cords

60°C Operating temperature

Colour-coded outlet and branch circuits for simple load balancing

Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52 mm wide x 53 mm deep on most models

Universal mounting system: Button mounting on rear and side + variable mounting system

Type

Rack PDU

Form factor

0U (Vertical)

Outlet control

No

Package contents

Rack PDU

Mounting accessories

Quickstart guide

Safety Instructions

Operating Temperature

0° to 60°C (32° to 140°F)

Mounting direction

Vertical

Color

Black

Material

Application notes

WUSD: Straight A's for K-12 virtualized environment

Application guide: Small data center power protection solutions

Eaton network closet solutions brochure

Eaton maintenance bypass application note

Brochures

Eaton ePDUs for office environments

Eaton ePDU G3 - Brochure

Eaton ePDU G3 one-page overview

Eaton UPS Services Quick Guide - EN

Eaton ePDU G3 brochure

Eaton UPS and battery services - EN

Eaton Flex and Hotswap MBP ePDU brochure

Case studies

Shawnigan Lake School: Boarding school protected by Eaton

LACCD: Eaton solution proves knowledge is power for college district

Certification reports

Eaton RoHS declaration of conformity: ePDU G3

Compliance information

EU Declaration of Conformity Eaton ePDUs G3

Drawings

EBAB19%20sk-34819-y1.pdf

Eaton Basic ePDU visio stencils

Installation instructions

Eaton ePDU G3 troubleshooting guide

Manuals and user guides

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 installation and connectivity quick start

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 operations manual

Eaton ePDU G3 - Installation and Connectivity Quick Start

White papers

Quick guide to power distribution

Optimizing rack power distribution

Aluminium

Input connection

C14

Cord length

3m

Wattage

2.3 kW max

Amperage Rating

10A

Input voltage

200-240V

Phase

Single-phase

Frequency rating

50/60 Hz

Outlets

(12) C13

Number of Outputs C13

12

Number of outlets with earth pin

12

SNMP

No

Ethernet interface

No

Serial interface

No

Mass configuration

No

Electrical connection

Connecting cord with plug

Mounting Dimension (metrical)

52

Mounting dimension (standardized)

Metric

Switchable

No

Over voltage category

2

Fitted with:

Mounting material



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia