

Xprinter®

07

10

0

XP-TT428B/TT436B

Thermal Transfer / Direct Thermal

FEATURES

- 1 Dual-motor, side clamshell design.
- 2 200 mm/s (8"/s) Printing Speed, make daily task more efficient;
- 3 300m ribbon capacity, up to 214 mm (8.4")OD label capacity design;
- 4 8MB Flash and 8MB SRAM memory
- 5 Compatible with TSPL/EPL/ZPL/DPL, perfect alternative for your barcode project;
- 6 Standard USB2.0 port
- 7 Bartender Label edit software & Windows driver available;
- 8 LCD control panel for optional, which allows user control the printer with repeat task without computer.

APPLICATION

- Printing
- Logistics & Warehouse
- Retail Marketing
- Manufacturing



BARCODE PRINTER — Xprinter®

Model	XP-TT428B	XP-TT436B
Resolution	203 DPI	300 DPI
Print method	Thermal Transfer / Direct Thermal	
Max.Print speed	200 mm (8") / s Max.	152 mm (6") / s Max.
Max.print width	104 mm (4.09")	
Max.print length	1778 mm (70")	889 mm (35")
Media		
Media type	Continuous, gap, black mark, fan-fold and punched hole	
Media width	25.4 mm ~ 115 mm	
Media thickness	0.06 mm ~ 0.25 mm	
Label length	10 - 1778 mm(0.39" ~ 70")	10 ~ 889 mm(0.39" ~ 35")
Label roll capacity	127 mm (5") OD (outside wound)	
Ribbon capacity	Max.300m	
Ribbon width	25.4mm-110mm (1"-4.3")	
Ribbon core inner diameter	25.4 mm (1")	
Performance Features		
Processor	32-bit CPU	
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb	
Interface	Standard:USB TF card Optional: Lan/WIFI/Bluetooth/Serial	
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor	
Fonts/Graphics/Symbologies		
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.	
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 , subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11	
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Rotation	0°、90°、180°、270°	
Emulaion	TSPL、EPL、ZPL、DPL	
Physical Features		
Dimension	246 mm (D) x 223 mm (W) x 204 mm (H)	
Weight	2.47kg	
Reliability		
Print head life	30 km	
Software		
Driver	Windows / Linux / Mac	
SDK	Windows / iOS / Android	
Power supply		
Input	AC 110-240V	
Output	DC 24V	
Options		
Factory Options	①RS-232C (2400-115200 bps) communication interface; ②Bluetooth module ③WiFi module ④Real clock ⑤Lan ⑥LCD/LED ⑦Cutter	
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder	
Environmental Conditions		
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing	
Storage environment	-40 ~ 60°C(-40~140°F) , Humidity:10 ~ 90% non-condensing	

