



VS412PT



Small distributor,golf,surface,4row,IP40,48M,MS-terminal,AUS,N+PE,white door

Technical properties

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

With a pipe-in lead	Yes
---------------------	-----

Configuration

Number of modules	48
-------------------	----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Electric current

Rated current	80 A
---------------	------

Dimensions

Depth of installed product	99 mm
----------------------------	-------

Internal depth	99 mm
----------------	-------

Height of installed product	647 mm
-----------------------------	--------

Width of installed product	282 mm
----------------------------	--------

Cover, door

Identification od protection index	40
------------------------------------	----

Interlockable	No
---------------	----

Number of keylock of the door	0
-------------------------------	---

Cover type	Closed (plain)
------------	----------------

Door locking	without
--------------	---------

Door leave	single
------------	--------

Cover type	Door
------------	------

Transparent cover or door	No
---------------------------	----

Materials

Colour	pure white
--------	------------

Colour	white
--------	-------

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Material	plastic
----------	---------

Type of surface treatment	untreated
---------------------------	-----------

Installation, mounting

Suitable for outdoor use	No
--------------------------	----

Settings

Enclosure type

Distributor empty cabinet

Equipment

Number of rows

4

Quantity of section in width

1

Quantity of rails

4

Can be accessorized

Yes

Number of openings for flange plates

0

Extension possible

Yes

Earthing terminal block

Yes

Neutral terminal block

Yes

Signal passing door

Yes

Standards

European directive WEEE

concerned

Safety

IK protection code against mechanical impacts

IK07

Protection index IP

IP40

Protection class

isol.class II

REACH conform

No

RoHS conform

Yes

Use conditions

Operating temperature

-25...40 °C