

PIXMA TS9551C
Specifications

Page by category ▼

[⏪ Back to product overview](#)

SHOP NOW

Specifications



A3 All-in-One printer



Auto 2-sided printing*

Auto 2-sided Print



Wireless and Ethernet connectivity

Connectivity



2-way paper feeding

2-way



5 individual inks

5 Individual Inks



Canon PRINT app



20-sheet ADF**



10.8cm (4.3 inch) touchscreen

Specifications in detail

General Specifications

Model Numbers

PIXMA TS9550 (BLACK)

PIXMA TS9551C (WHITE)¹

Functions

Wireless / Ethernet, Print, Copy, Scan, Cloud Link

Printer Specifications

Print Resolution

Up to 4800² x 1200 dpi

Print Technology

5 Individual Ink Tanks (PGBK, BK, C, M, Y)

ChromaLife100 inks

Mono Print Speed

Approx. 15.0 ipm³

Colour Print Speed
Approx. 10.0 ipm⁴

Photo Print Speed
Borderless 10x15cm : Approx. 21 seconds⁵

Borderless Printing
Yes (A3, A4, Letter, 20x25cm, 13x18cm, 10x15cm, 13x13cm, 8.9x8.9cm, 10x10cm, 17.5x25cm, 25x30cm, 30x30cm)

Two Sided Printing
Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

Direct Disc Printing
Yes

Cartridges And Yields

Standard Ink Cartridges
5 individual ink tanks
PGI-580PGBK (Pigment Black)
CLI-581BK (Black)
CLI-581C (Cyan)
CLI-581M (Magenta)
CLI-581Y (Yellow)

Optional XL Ink Cartridges
High yield XL ink tanks
PGI-580PGBK XL (Pigment Black)
CLI-581BK XL (Black)
CLI-581C XL (Cyan)
CLI-581M XL (Magenta)
CLI-581Y XL (Yellow)

Optional XXL Ink Cartridges
High yield XL ink tanks
PGI-580PGBK XXL (Pigment Black)
CLI-581BK XXL (Black)
CLI-581C XXL (Cyan)
CLI-581M XXL (Magenta)
CLI-581Y XXL (Yellow)

Ink Tanks Yield (Plain paper)
A4 Colour Document⁶
Pigment Black: 200 pages
Pigment Black XL: 400 pages
Pigment Black XXL: 600 pages
Black: 1451* pages
Black XL: 3120* pages
Black XXL: 6360* pages
Cyan: 256 pages

Cyan XL: 515 pages
Cyan XXL: 820 pages
Magenta: 237 pages
Magenta XL: 474 pages
Magenta XXL: 760 pages
Yellow: 257 pages
Yellow XL: 514 pages
Yellow XXL: 824 pages
* Estimated supplemental yield

Ink Tanks Yield (Photo print)
10x15cm photo⁷
Pigment Black: 1263* photos
Pigment Black XL: 3373* photos
Pigment Black XXL: 5500* photos
Black: 231* photos
Black XL: 520* photos
Black XXL: 858* photos
Cyan: 83 photos
Cyan XL: 170 photos
Cyan XXL: 282 photos
Magenta: 108 photos
Magenta XL: 225 photos
Magenta XXL: 367 photos
Yellow: 99 photos
Yellow XL: 199 photos
Yellow XXL: 322 photos
* Estimated supplemental yield

Paper Support

Paper Types
Plain Paper
Canon High Resolution Paper (HR-101N)
Canon Pro Platinum (PT-101)
Canon Plus Glossy II (PP-201)
Canon Pro Luster (LU-101)
Canon Plus Semi-gloss (SG-201)
Canon "Everyday Use" (GP-501)
Canon Matte (MP-101)
Envelopes
Other Fine Art Papers
Printable Discs
Removable Photo Stickers (RP-101)
Magnetic Photo Paper (MG-101)

Maximum Paper Input
Rear Tray: Max. 20 sheets (photo paper) or Max. 100 sheets A4/ 50 sheets A3 (plain paper)
Front Cassette: Max. 100 sheets (plain paper)
Multi-purpose Tray: Printable Nail Stickers (NL-101)/1 printable CD, DVD or Blu-Ray Disc

Paper Size

Rear Tray:

A3/A4/A5/B5/LTR/LGL/20x25cm/13x18cm/10x15cm/13x13cm/8.9x8.9cm/10x10cm/17.5x25cm/25x30cm/30x30cm,
Envelopes(DL,COM10)

[Custom size] width 55mm - 304.8 mm, length 89mm - 676mm

Front Cassette: A4, A5, B5, LTR

[Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm

Paper Weight

Rear Tray: Plain paper 64 - 105 g/m², Canon photo paper up to 300 g/m²

Front Cassette: Plain Paper: 64-105 g/m²

Scanner Specifications

Scanner Type

Flatbed, ADF and CIS colour scanner

Scanner Resolution (Optical)

1200 x 2400 dpi⁸

Scanning Depth (Input / Output)

Colour: RGB each 16bit/8bit

Greyscale: 16 bit / 8 bit

Maximum Document Size

Flatbed: A4, LTR (216x297mm)

ADF: A4, LTR, LGL

Copier Specifications

Copy Speed

sFCOT: Approx. 19sec⁹

sESAT: Approx. 6.5ipm¹⁰

sESAT ADF: Approx. 8.0 ipm¹¹

Multiple Copy

max. 99 pages

Copy Functions

Document Copying, Photo Copying, Borderless copy, 2-sided copy, 2-on-1
and 4-on-1 copy, Frame erase copy, Disc Label Copy, ID copy

Copy Zoom

25 - 400% (in 1% increments)

Fit to page

A5 to A3, B5 to B4, A4 to A3, A5 to A4, B5 to A4, A4 to B5, A4 to A5

Interface

Display Type & Size

10.8cm LCD (TFT colour/Touch)

Display Languages

33 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/Portuguese/Norwegian/Swedish/Danish/Finnish/Russian/Czech/Hungarian/Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/Thai/Croatian/Vietnamese

Automatic Document Feeder

Up to 20 Sheets (1-sided)

Interface Type - PC / Mac

Hi-Speed USB (B Port)

Ethernet: 10/100Mbps (auto switchable)

Wi-Fi: IEEE802.11 b/g/n/a

Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP, Administration password

Wireless LAN Frequency Band: 2.4GHz

Interface Type - Other

Canon PRINT Inkjet/SELPHY app

Bluetooth

Message In Print app

Nail Sticker app

PIXMA Cloud Link

Canon Print Service Plugin (Android)

Google Cloud Print

Apple AirPrint

Wireless Direct

Access Point Mode

LAN/WLAN PictBridge

Memory Card Slot

Mopria (Android)

Compatible OS

SD Card, SDHC Card, SDXC Card, miniSD Card*, micro SD Card*

mini SDHC Card*, micro SDHC Card*, microSDXC Card*

*Using recommended adapter - not supplied

Software

Supported Operating Systems

Windows 10、Windows 8.1、Windows 7 SP1

Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.

.NET Framework 4.5.2 or 4.6 is required
OS X 10.10.5 ~ OS X 10.11 、 macOS 10.12 ~ macOS 10.13

Supported Mobile Systems
iOS, Android, Windows 10 Mobile

Minimum System Requirements
Windows: 3.1GB disk space, Internet Explorer 8
Mac: Internet connection, 1.5GB disk space, Safari 5
Display: 1024 x 768 XGA

Software Included
MP Driver including Scanning Utility
Easy-WebPrint EX (download) ¹²

Physical Features

Weight
approx. 9.7kg

Dimensions
approx. 468 x 366 x 193 mm

Acoustic noise levels
approx. 49.5dB(A) ¹³

Recommended Operating Environment
Temperature: 15-30°C
Humidity: 10-80%RH (no dew condensation)

Power Source
AC 100-240V, 50/60Hz

Power Consumption
Off: Approx. 0.3W
Standby (connected to PC via USB): Approx. 1.2W (scanning lamp off)
Standby (all ports connected): Approx. 2.0W (scanning lamp is off)
Time to enter Standby mode: 10min 56sec
Copying: Approx. 14W ¹⁴

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

1. Some colours may not be available in your region.
2. Ink droplets can be placed with a minimum pitch of 1/4800 inch
3. A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.
4. A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.
5. Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
6. Declared yield value in accordance with ISO/IEC 24711 standard. Values obtained by continuous printing.
7. Declared yield value in accordance with ISO/IEC 29102. Values obtained by continuous printing.
8. Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
9. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
10. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
11. Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
12. Easy-WebPrint EX requires Internet Explorer 8 or later
13. When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
14. Some colours may not be available in your region.

*(A5/A4/LTR size plain paper only)