



FORCE 165 230V ACX PLASTIC CARRY CASE



Overview

FORCE 165 230V ACX PLASTIC CARRY CASE

cod. 815857

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 815857	A_{MAX}	MAX ABSORBED CURRENT 31 A	V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V
P_{MAX}	MAX ABSORBED POWER 4,1 kW	IP	PROTECTION DEGREE IP21	F	MAINS FREQUENCY 50 / 60 Hz
P_{GEN}	MOTORGENERATOR MINIMUM POWER 6 kW	W_LH_L	DIMENSIONS 38 x 42 x 17 cm	A_{MIN} A_{MAX} DC	CURRENT RANGE 10 - 150 A
FUSE	MAINS FUSE 16 A	kg	WEIGHT 5,5 kg	%USE_{20°C}	%USE (20°C USE) 60% @ 150A %
η	EFFICIENCY 82 V	BAR CODE	EAN CODE 800489778955 2	A_{MAX} 40°C DC	MAX CURRENT DC (EN 60974-1) 140 @ 7% A
φ	POWER FACTOR (cosphi) 0,6	PIECES/PALLET	PIECES/PALLET 36 pz/pallet	V₀ DC	MAX NO LOAD VOLTAGE 72 V



FORCE 165 230V ACX PLASTIC CARRY CASE



D. USABLE ELECTRODES IN DC 1,6 - 4 mm

(*)%USE:DATUM CREATED BY TELWIN,

Included Accessories

CABLE 16 MMQ 1,8 M - DINSE 25 - 124508

PLASTIC CARRY CASE - 322800



TOLEDO 250 WORK CLAMP 250A - 712030



SLAG REMOVER - 712139



DALLAS 300 ELECTRODE HOLDER 300A - 712260