



HP Smart Tank 580 All-in-One Printer (1F3Y2A)

Overview



Enjoy everyday reliability with the HP quality you expect and savings that are anything but expected[1]

Enjoy everyday reliability with the HP Smart Tank 580 All-in-One Printer that delivers HP quality you expect and savings that are anything but expected[1]

Smart tank value

Up to 18,000 pages of black or 6,000 pages of colour ink keeps you printing at a fraction of the cost[2,1]

Conveniently intuitive

Easy mobile-guided setup [5]

Ready when you are

Stay connected and keep printing with self-healing Wi-Fi [4]

Features

Mobile-guided, seamless setup⁵

Smart buttons

Low-on-ink sensors

Self-healing Wi-Fi⁴

HP Smart Advance⁵

HP Auto On/Auto-Off technology³

[1] HP ink bottles compared to HP ink cartridges. Cost per page based on expected black and composite (cyan/magenta/yellow) page yield results based on HP methodology and continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see hp.com/go/learnaboutsupplies

[2] Based upon 200 pages per month of HP Smart Tank customers' usage. Actual yield varies considerably based on content of printed pages and other factors. Average based on ISO/IEC 24711 or HP testing methodology and continuous printing. Some ink from included bottles is used to start up the printer. For details, see: www.hp.com/go/learnaboutsupplies

[4] Wireless operations are compatible with 2.4 GHz operations only. Learn more at www.hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®.

[5] Requires the HP Smart app download. For details on local printing requirements see www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. For details, see: www.HPSmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. Fax capabilities are for sending a fax only.

Specifications

Print quality black (best)	Up to 1200 x 1200 rendered dpi
Print quality color (best)	Up to 4800 x 1200 optimized dpi color (when printing from a computer and 1200 input dpi)
Print speed black (ISO, A4)	Up to 12 ppm
Print Speed Color (ISO)	Up to 5 ppm
Print speed	Print speed up to 12 ppm (black) and 5 ppm (color)
Functions	Print, copy, scan
Duplex printing	Manual (driver support provided)
Duty cycle (monthly, A4)	Up to 3,000 pages
Duty cycle (monthly, letter)	Up to 3,000 pages
Energy savings feature technology	HP Auto-Off Technology
Replacement cartridges	North America: HP GT53 90-ml Black Original Ink Bottle 1VV22AA; HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA; HP GT52 Cyan Original Ink Bottle MOH54AA; HP GT52 Magenta Original Ink Bottle MOH55AA; HP GT52 Yellow Original Ink Bottle MOH56AA; Europe Middle East and Africa: HP GT53XL 135-ml Black Original Ink Bottle 1VV21AE; HP GT52 Cyan Original Ink Bottle MOH54AE; HP GT52 Magenta Original Ink Bottle MOH55AE; HP GT52 Yellow Original Ink Bottle MOH56AE; Asia Pacific: HP GT53 90-ml Black Original Ink Bottle 1VV22AA; HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA; HP GT52 Cyan Original Ink Bottle MOH54AA; HP GT52 Magenta Original Ink Bottle MOH55AA; HP GT52 Yellow Original Ink Bottle MOH56AA; Latin America: HP GT53 90-ml Black Original Ink Bottle 1VV22AL; HP GT52 Cyan Original Ink Bottle MOH54AL; HP GT52 Magenta Original Ink Bottle MOH55AL; HP GT52 Yellow Original Ink Bottle MOH56AL; HP GT52 3-pack Cyan/Magenta/Yellow Original Ink Bottles X4E44AL. For more information about fill and yield, see http://www.hp.com/go/learnaboutsupplies .
Connectivity, standard	1 Hi-Speed USB 2.0 (device); 1 Wi-Fi 802.11b/g/n; 1 Wi-Fi Direct
Network capabilities	Yes (via WiFi)
Wireless capability	Yes, built-in Wi-Fi 2.4G, Wi-Fi Direct
Mobile printing capability	HP Smart app; Apple AirPrint; Mopria Print Service; HP Print Service Plugin (Android printing); Wi-Fi Direct Printing
Software included	HP Printer Software
Compatible Operating Systems	Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey (<i>Microsoft Windows 11, 10; macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; Android; iOS;</i>)
Sustainable impact specifications	45% post-consumer recycled plastic; EPEAT® registered
Energy star certified	No
Digital sending standard features	Scan to file (from software); HP Smart Tasks
Scan file format	JPEG; PDF

Scan input modes	Copy; HP Software; EWS
Scan technology	Contact Image Sensor (CIS)
Scanner type	Flatbed only
Display	33 segments + 1.2-inch iCON LCD Display
Minimum dimensions (W x D x H)	434.66 x 361.53 x 157.26 mm
Minimum dimensions (W x D x H)	17.11 x 14.23 x 6.19 in
Weight	5.03 kg
Weight	11.09 lb
Power consumption	0.109 watts (manual-Off), 3.023 watts (ready), 1.096 watt (sleep) ^[2]
Power supply type	Internal built in
What's in the box	HP Smart Tank 580 All-in-One Printer; 3 x HP GT53XL 135-ml Black Original Ink Bottle (1VV24A); HP GT52 50-ml Cyan Original Ink Bottle (6ZE03A); HP GT52 50-ml Magenta Original Ink Bottle (6ZE04A); HP GT52 50-ml Yellow Original Ink Bottle (6ZE05A); HP Black Original Printhead (M0H50A); HP Tri-Color Original Printhead (6ZA18AE); Setup Guide; Reference Guide; Ink Caution flyer; Regulatory flyer; Warranty flyer; Power Cord; For more information about fill and yield, see https://www.hp.com/go/learnaboutsupplies
Manufacturer Warranty	One-year or 30,000 pages limited hardware warranty, whichever is earlier from the date of purchase and get up to 2 years extended warranty upon registration at https://www.hp.com/go/inkTank-SmartTank-warranty . User replaceable parts have separate warranty periods.

Additional specifications

Accessories	None
Acoustic power emissions (active, printing)	6.4 B(A)
Acoustic pressure emissions	56.8 dBA
Additional information about HP	https://www.hp.com
Additional information about HP in the countries	https://www.hp.com/uk
Automatic paper sensor	No
Bit depth	24-bit
Borderless printing	Yes (up to 8.5 x 11 in, 210 x 297 mm)
Bottom margin (A4)	3 mm
Cable included	No, please purchase USB cable separately.
Cartons per layer	12
Color copy capability	Yes
Color or black	Color
Color scanning	Yes
Color(s) of printing supplies	Black; Cyan; Magenta; Yellow
Connection type	Wireless
Control panel	Power On/Off, Cancel, Resume, Color Copy, Black copy, ID copy, WI-FI and Info button
Copier settings	Number of Copies, Resize, Quality, Lighter/Darker, Papersize, Papertype, ID Copy, Enhancement
Copies, maximum	Up to 99 copies
Copy reduce / enlarge settings	Via HP Smart app
Copy resolution (black graphics)	Up to 1200 dpi
Copy resolution (black text)	Up to 1200 dpi
Copy resolution (color text and graphics)	Up to 1200 x 1200 dpi reduced speed
Copy speed black (ISO)	Up to 10 cpm
Copy speed color (ISO)	Up to 2 cpm
Count of layers in pallet	5
Country of origin	Made in China
Datasheet photo 1	Publication photos/LEBI_WL_580_LightBasalt wyh.jpg
Datasheet photo 4	Publication logos/Easy_setup wyh.jpg
Datasheet photo 5	Publication logos/Auto_on-off wyh.jpg

Dimensions with trays up (W x D x H)	434.66 x 361.53 x 157.26 mm
Electromagnetic compatibility	EN 55032:2015+A11:2020 Class B; EN 55024:2010 +A1:2015; EN 55035:2017+A11:2020; EN IEC 61000-3-2:2019; EN 61000-3-2:2014; EN 61000-3-3:2013 +A1:2019; EN 301 489-1 V2.2.3; EN 301 489-17 V3.2.4
Enhanced scanning resolution	Up to 1200 dpi
Envelope Feeder	No
File Format Supported	JPG; PDF
Finished output handling	Sheetfed
First page out black (A4, ready)	As fast as 14 sec
First page out color (A4, ready)	As fast as 21 sec
First page out footnote	For details see: http://www.hp.com/go/printerclaims
Fonts and typefaces	None
Geographic availability	EM
Image scaling or enlargement range	25 to 150%
Ink types	Pigment-based (black); Dye-based (color)
Input capacity	Up to 100 sheets
Left margin (A4)	3 mm
Levels of grayscale	256
Mac compatible	Yes
Maximum Input Capacity (envelopes)	Up to 10 envelopes
Maximum Memory	64MB
Maximum dimensions (W x D x H)	17.11 x 22.86 x 10.21 in
Maximum dimensions (W x D x H)	434.66 x 580.65 x 259.37 mm
Maximum input capacity (10x15cm photos)	Up to 30 sheets
Maximum input capacity (4x6 photo)	Up to 30 sheets
Maximum input capacity (cards)	Up to 30 cards
Maximum input capacity (labels)	Up to 10 sheets
Maximum input capacity (photo paper)	Up to 30 sheets
Maximum input capacity (sheets)	Up to 100 sheets
Maximum output capacity (cards)	Up to 30 cards
Maximum output capacity (envelopes)	Up to 10 envelopes
Maximum output capacity (labels)	Up to 30 sheets

Maximum output capacity (photo paper)	Up to 30 sheets
Maximum output capacity (sheets)	Up to 30 sheets
Maximum print area	216 x 355 mm
Media sizes supported	Letter; legal; 4 x 6 in; 5 x 7 in; 8 x 10 in; No. 10 envelopes
Media sizes supported	A4; B5; A6; DL envelope, legal
Media sizes supported, key	4 x 6 in; Letter; Legal; Envelopes
Media sizes supported, key	10 x 15 cm; A4; Envelopes
Media sizes, custom	3.5 x 5 in to 8.5 x 14 in
Media sizes, custom	88.9 x 127 to 215.9 x 355.6 mm
Media types	Plain paper, Matte Brochure Papers, Glossy Brochure Papers, Photo papers, Envelopes, Other specialty inkjet papers
Media weight, recommended	75 g/m ²
Media weight, recommended	20 lb
Media weight, supported	Plain paper: 60 to 90 g/m ² ; Envelopes: 75 to 90 g/m ² ; Cards: up to 200 g/m ² ; Photo paper: up to 300 g/m ²
Media weight, supported	Plain paper: 16 to 24 lb; Envelopes: 20 to 24 lb; Cards: up to 110 lb; Photo paper: up to 80 lb
Memory	64 MB Integrated DDR1
Memory Slots	No
Minimum System Requirements	Microsoft® Windows® 11, 10; Internet connection, Microsoft® Internet Explorer or Edge.
Minimum System Requirements for Macintosh	Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB HD; Internet required
Model number	580
Non-Operating Humidity Range	5 to 90% RH (non-condensing)
Number of print cartridges	4 (1 each black bottle, set of 3 color bottles)
Number of users	1-3 Users
Operating humidity range	15 to 80% RH (non-condensing)
Operating temperature range	41 to 104°F
Operating temperature range	5 to 40°C

Orderable supplies

North America: HP GT53 90-ml Black Original Ink Bottle 1VV22AA; HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA; HP GT52 Cyan Original Ink Bottle M0H54AA; HP GT52 Magenta Original Ink Bottle M0H55AA; HP GT52 Yellow Original Ink Bottle M0H56AA; Europe Middle East and Africa: HP GT53XL 135-ml Black Original Ink Bottle 1VV21AE; HP GT52 Cyan Original Ink Bottle M0H54AE; HP GT52 Magenta Original Ink Bottle M0H55AE; HP GT52 Yellow Original Ink Bottle M0H56AE; Asia Pacific: HP GT53 90-ml Black Original Ink Bottle 1VV22AA; HP GT53XL 135-ml Black Original Ink Bottle 1VV21AA; HP GT52 Cyan Original Ink Bottle M0H54AA; HP GT52 Magenta Original Ink Bottle M0H55AA; HP GT52 Yellow Original Ink Bottle M0H56AA; Latin America: HP GT53 90-ml Black Original Ink Bottle 1VV22AL; HP GT52 Cyan Original Ink Bottle M0H54AL; HP GT52 Magenta Original Ink Bottle M0H55AL; HP GT52 Yellow Original Ink Bottle M0H56AL; HP GT52 3-pack Cyan/Magenta/Yellow Original Ink Bottles X4E44AL. For more information about fill and yield, see <http://www.hp.com/go/learnaboutsupplies>.

Output capacity	Up to 30 sheets
Output file format	JPEG
Package dimensions (W x D x H)	495 x 198 x 478 mm
Package dimensions (W x D x H)	19.49 x 7.8 x 18.82 in
Package weight	15.89 lb to 16.73 lb depending on number of bottle/s included
Package weight	7.2 kg to 7.6 kg depending on number of bottle/s included
Page yield (set-up/inbox cartridges)	~6000 pages black, ~6,000 pages cyan, magenta, yellow composite yield ~12000 pages black, ~6,000 pages cyan, magenta, yellow composite yield ~18000 pages black, ~6,000 pages cyan, magenta, yellow composite yield
Pallet dimensions	47.99 x 40 x 94.09 in
Pallet dimensions (W x D x H)	1200 x 1000 x 2390 mm
Pallet weight	950 lb to 1002 lb depending on number of bottle/s included
Pallet weight	432 kg to 455 kg depending on number of bottle/s included
Paper handling input, standard	100-sheet input tray
Paper handling output, standard	30-sheet output tray
Paper trays, maximum	1
Paper trays, standard	1
Photo (product photo, jpg, 70x100)	Printers and Multifunction/CD028B_70x100.jpg
Photo proofsheets supported	No
PictBridge description	No
PictBridge supported	No
Plug and play	Auto Wireless Connect
Power	Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). High voltage: Input voltage 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3Hz)
Print Technology	Ink
Print colors	Yes

Print colors maximum	4
Print head nozzles	704 (Black), 588 (Tri-color)
Print heads	2 (1 each black, tri-color)
Print languages	HP PCL 3 GUI; HP PCLm (HP Apps/UPD); URF (AirPrint)
Print speed black (ISO)	Up to 12 ppm
Print speed black (draft, A4)	Up to 22 ppm
Print speed color (ISO)	Up to 5 ppm
Print speed color (draft, A4)	Up to 16 ppm
Print speed color (normal, 10x15 photo)	As fast as 76 sec
Print speed color (normal, 4x6 photo)	As fast as 76 sec
Print technology	HP Thermal Inkjet
Printer Management	No
Printer drivers included	HP PCL 3 GUI
Processor speed	980 MHz
Product color	Light basalt
Product logos	Air Print; Android; Windows; USB high speed; WiFi certified; Mopria; PAP 20; SmartWay; Fragile; Keep out of Rain; This side up; EPEAT Silver; EnergyStar
Product name (back)	Smart Tank 580 Wireless All-in-One
Product name (front)	Smart Tank 580 Wireless All-in-One
Product name (primary)	Smart Tank 580 Wireless All-in-One
Product name (secondary)	Smart Tank 580 Wireless All-in-One
Product short name specifications	HP Smart Tank 580 All-in-One Printer, Color, Printer for Home and home office, Print, copy, scan, Wireless; High-volume printer tank; Print from phone or tablet; Scan to PDF
Quantity per pallet	60
Recommended Macintosh system requirements	Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB HD; Internet required
Recommended monthly page volume	400 to 800
Recommended operating humidity range	20 to 80% RH
Recommended operating temperature range	15 to 30°C
Recommended operating temperature range	59 to 86°F

Replacement cartridges footnote	Black and composite color average per bottle (cyan/magenta/yellow) results based on HP methodology from the simulation of continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. An additional black ink bottle is required to print 8,000 color test pages. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see http://www.hp.com/go/learnaboutsupplies .
Right margin (A4)	3 mm
Safety	IEC 60950-1 & IEC62368-1 compliant; EU RED and EN 60950-1 & EN 62368-1 compliant; Singapore Safety; China CCC; Taiwan BSMI
Scan resolution, hardware	Up to 1200 x 1200 dpi
Scan resolution, optical	Up to 1200 dpi
Scan size, maximum	216 x 297 mm
Scan size, maximum	8.5 x 11.69 in
Scanning options (ADF)	Not Applicable
Security management	No
Segment (filter)	Home and home office
Send to email capability	No
Service & support options	Protect your investment—HP Total Care offers a variety of extended warranties and services, go to http://www.hp.com/support
Standard input capacity (cards)	Up to 30 cards
Standard input capacity (envelopes)	Up to 10
Standard input capacity (legal)	Up to 100 sheets
Standard media sizes (duplex)	A4; B5
Standard media sizes (duplex, imperial)	Letter; Executive
Standard output capacity (cards)	Up to 30 cards
Standard output capacity (envelopes)	Up to 10 envelopes
Standard output capacity (labels)	Up to 10 sheets
Standard output capacity (legal)	Up to 30 sheets
Storage altitude	4572 m
Storage altitude	15,000 ft
Storage device and direct print support	Wireless Direct Printing
Storage temperature range	-40 to 140°F
Storage temperature range	-40 to 60°C
Sub-brand name	Smart Tank

System requirements, recommended	Microsoft® Windows® 11, 10; Internet connection, Microsoft® Internet Explorer or Edge.
Target user and print volume	For teams up to 3 users; Prints up to 800 pages/month
Technology logo 2	Publication logos/logo_android.jpg
Technology logo 3	Publication logos/Epeat silver.jpg
Technology logo 4	Publication logos/IF_DesignAward_2023_logo.jpg
Technology logo 5	Publication logos/Red Dot 2023_logo.jpg
Technology logo 6	AHID/38dec1d59a27468459a4292596927607e6c055b3
Technology logo 7	AHID/619a3448a77fd810ffc2ecd1be2266a1ade2bab4
Telecom compliance (fax capability)	EN 300 328 V2.2.2; EN 301 893 V2.1.1; EN 300 440 V2.1.1
Top key features	Wireless; High-volume printer tank; Print from phone or tablet; Scan to PDF
Top margin (A4)	3 mm
Twain version	Version 2.4
UNSPSC code	43212104
UPC number	(ABT) 196548866786; (BEW) 196068963514
Vertical alignment accuracy	+/- 0.0008 in
Vertical alignment accuracy	+/- 0.02 mm
Video action printing supported	No
Wireless technologies	802.11b/g/n

[2] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

Services

HP Care Pack Services

★ : Recommended

Imaging and Printing Consumer Care Pack Services

HP 2 year Return to Depot Service for MFP Page Limit	U9NR5E
HP 3 year Return to Depot Service for MFP Page Limit	UA5C2E

Ink Supplies

★ : Recommended

HP Inkjet Printer Cartridges and Ink Supplies

HP 6ZA17AE Black Printhead	6ZA17AE
HP 6ZA18AE Tri-color Printhead	6ZA18AE

HP Ink Bottles

HP GT52 Cyan Original Ink Bottle	M0H54AE
HP GT52 Magenta Original Ink Bottle	M0H55AE
HP GT52 Yellow Original Ink Bottle	M0H56AE
HP GT53XL 135-ml Black Original Ink Bottle	1VV21AE

HP Photo Papers

HP Photo Papers for inkjet

HP Matte Photo Paper, 180 g/m2, 10 x 15 cm (101 x 152 mm), 25 sheets	7HF70A
--	--------

Disclaimer — Copyright

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.