

MAGMA

מסכות ריתוך עם מסנן אוויר

FreFlow™ V3



הגנה על דרכי הנשימה

יעילות מסנן < 99.97%

מונעת שאיפה של אבק,

מזהמים, חלקיקים עדינים ומזהמים אחרים

אספקת אוויר חכמה

מכונת הנשמה תתאים את קצב הזרימה

באופן אוטומטי בהתאם לחסימה של המסנן

מחווני תצוגה בזמן אמת

מחווני מצב מסנן / קצב זרימת אוויר

/ קיבולת סוללה,

ניסור ותצוגה בזמן אמת.

מערכת אדקעה אוטומטית

מחווני מהבהב, צליל צפצוף,

יחד עם מפוח רוסט

להבטחת בטיחות

עיצוב ראש מתרומם

הרמה קלה לפונקציית השחזה,

מתאימה למצב ריתוך

חיתוך / השחזה

שדה ראייה פנוראמי גדול שטח של

12X20 ס"מ,

עדשה גדולה שקופה ומעוקלת נגד

ערפל ו שחיקה

סוללה ליתיום נטענת

לח"י סוללה ארוכים יותר אפשרות טעינה

מהירה הופכת את הטעינה לשעה אחת

בלבד



MMA



MIG/MAG



TIG



FLUX-CORED



PLASMA



GRINDING

ADF Specifications

מפרט מסכה

Optical Class	1 / 1 / 1 / 1
Viewing Area	(75 mm (4.21" x 2.95 107
Cartridge Size	(129 x 83 mm (6.14" x 4.84" x 1.30 156
Arc Sensor	4
Light State	DIN 4
Grind State	DIN 4
Cutting Shade	Shade No. from 5 to 8
Welding Shade	Shade No. from 9 to 13
Shade Control	Internal, Digital Display Control
Power On / Off	Automatic On / Off
Sensitivity Control	Low ~ High, Digital Display Control
UV / IR Protection	Up to Shade DIN16 at all times
Power Supply	Solar cell. Battery replaceable, 2 x CR2450 lithium battery
Switching Time	s. from Light to Dark 1/25,000
Grinding	Yes
(Delay (Dark to Light	s. Digital Display Control 1.0 ~ 0.1
Low Amperage TIG Rated	(amps (DC): ≥ 2 amps (AC 2 ≥
.Operating Temp	(C ~ +55 °C (14 °F ~ 131 °F 10-
.Storing Temp	(C ~ +70 °C (- 4 °F ~ 158 °F 20-
Helmet Material	High Impact Resistance Nylon
Approved	CE SF ANSI AS/NZS

Respiratory Welding Helmet



Easy Operation



Hard Hat Adapter



Curved 3D Feature



High-Impact Resistance



Wide Application



Patented Headgear



Applicable with PAPR



Side Lens

Filter efficiency

99.97%



WWW.GAIA.CO.IL

גאיה מכונות בע"מ