

# **Modern MD342CQPW**

BE YOUR WINDOW TO THE WORLD





#### **SPECIFICATIONS**

PANEL RESOLUTION         3440 x 1440 (UWQHD)           REFRESH RATE         120Hz           RESPONSE TIME         1ms (MPRT) / 4ms (GtG)           PANEL TYPE         VA           BRIGHTNESS (NITS)         300 cd/m²           VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         21:9           CUNTAURE         1500R           CONTRAST RATIO         3500:1           ADOBE RGB / DCI-P3 / SRGB         92% / 95% /119%           ACTIVE DISPLAY AREA (MM)         797.22 (H) x 333.72 (V)           PIXEL PITCH (H X V)         0.23175 (H) x 0.23175 (V)           SURFACE TREATMENT         Anti-Glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8bits + FRC)           HDR Ready         2x HDMI™ 2.0b (UWQHD@100Hz)           VIDEO PORTS         1x USB 5Gbps Type-B           2x USB 5Gbps Type-B         2x USB 5Gbps Ty	PANEL SIZE	34"
RESPONSE TIME  PANEL TYPE  VA  BRIGHTNESS (NITS)  300 cd/m²  VIEWING ANGLE  178°(H) / 178°(V)  ASPECT RATIO  21:9  CURVATURE  1500R  CONTRAST RATIO  3500:1  ADOBE RGB / DCI-P3 / SRGB  92% / 95% / 119%  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  1.07B  COLOR BIT  10 bits (8bits + FRC)  HDR Ready  VIDEO PORTS  1x HDMI™ 2.0b (UWQHD@100Hz)  1x DisplayPort 1.4a  1x Type-C (DP Alt.) w/ 98W PD  USB Ports  1x USB 5Gbps Type-B  2x USB 5Gbps Type-B  2x USB 5Gbps Type-A  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK  Yes  PEAKER  2x 3W  VESA MOUNTING  75 x 75 mm  POWER TYPE  External Adaptor 19V 9.47A  POWER INPUT  100~240V, 50~60Hz  DYNAMIC REFRESH RATE  TECHNOLOGY  ADJUSTMENT (TILT)  -5° ~ 20°  ADJUSTMENT (TILT)  -5° ~ 5°  ADJUSTMENT (HEIGHT)  0 ~ 110 mm  B08.6 x 424.1 x 250.6 mm  (31.83 x 16.70 x 9.87 inch)  PASS S 510 x 245 mm  (37.2 x 20.1 x 9.7 inch)	PANEL RESOLUTION	3440 x 1440 (UWQHD)
PANEL TYPE         VA           BRIGHTNESS (NITS)         300 cd/m²           VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         21:9           CURVATURE         1500R           CONTRAST RATIO         3500:1           ADOBE RGB / DCI-P3 / SRGB         92% / 95% /119%           ACTIVE DISPLAY AREA (MM)         797.22 (H) x 333.72 (V)           PIXEL PITCH (H X V)         0.23175 (H) x 0.23175 (V)           SURFACE TREATMENT         Anti-Glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8bits + FRC)           HDR Ready         2x HDMI™ 2.0b (UWQHD@100Hz)           VIDEO PORTS         1x USB 5Gbps Type-B           1x USB 5Gbps Type-B         2x USB 5Gbps Type-B           2x USB 5Gbps Type-B	REFRESH RATE	120Hz
BRIGHTNESS (NITS)   300 cd/m²     VIEWING ANGLE   178°(H) / 178°(V)     ASPECT RATIO   21:9     CURVATURE   1500R     CONTRAST RATIO   3500:1     ADOBE RGB / DCI-P3 / SRGB   92% / 95% / 119%     ACTIVE DISPLAY AREA (MM)   797.22 (H) x 333.72 (V)     PIXEL PITCH (H X V)   0.23175 (H) x 0.23175 (V)     SURFACE TREATMENT   Anti-Glare     DISPLAY COLORS   1.07B     COLOR BIT   10 bits (8bits + FRC)     HDR Ready   2x HDMI™ 2.0b (UWQHD@100Hz)     IX DisplayPort 1.4a   1x Type-C (DP Alt.) w/ 98W PD     USB PORTS   1x USB 5Gbps Type-B   2x USB 5Gbps Type-A     AUDIO PORTS   1 x Headphone-out     KENSINGTON LOCK   Yes     SPEAKER   2x 3W     VESA MOUNTING   75 x 75 mm     POWER TYPE   External Adaptor 19V 9.47A     POWER INPUT   100~240V, 50~60Hz     DYNAMIC REFESH RATE   TECHNOLOGY   ADJUSTMENT (TILT)   -5° ~ 20°     ADJUSTMENT (TILT)   -5° ~ 30°     ADJUSTMENT (FIVOT)   -5° ~ 5°     ADJUSTMENT (HEIGHT)   0 ~ 110 mm     DIMENSION (W X H X D)   808.6 x 424.1 x 250.6 mm   (31.83 x 16.70 x 9.87 inch)     CARTON DIMENSION (W X H X D)   945 x 510 x 245 mm   (37.2 x 20.1 x 9.7 inch)	RESPONSE TIME	1ms (MPRT) / 4ms (GtG)
VIEWING ANGLE   178°(H) / 178°(V)	PANEL TYPE	VA
ASPECT RATIO  CURVATURE  1500R  CONTRAST RATIO  3500:1  ADOBE RGB / DCI-P3 / SRGB  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  VIDEO PORTS  1x HDMI™ 2.0b (UWQHD@100Hz)  1x USB 5Gbps Type-B  2x USB 5Gbps Type-B  2x USB 5Gbps Type-A  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK  SPEAKER  VESA MOUNTING  POWER TYPE  External Adaptor 19V 9.47A  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (FIEIGHT)  DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  24 95% /119%  3500:1	BRIGHTNESS (NITS)	300 cd/m²
CURVATURE         1500R           CONTRAST RATIO         3500:1           ADOBE RGB / DCI-P3 / SRGB         92% / 95% /119%           ACTIVE DISPLAY AREA (MM)         797.22 (H) x 333.72 (V)           PIXEL PITCH (H X V)         0.23175 (H) x 0.23175 (V)           SURFACE TREATMENT         Anti-Glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8bits + FRC)           HDR Ready         2x HDMI™ 2.0b (UWQHD@100Hz)           VIDEO PORTS         1x USB 5Gbps Type-B           1x USB 5Gbps Type-B         2x USB 5Gbps Type-B           2x USB 5Gbps Type-A         2x USB 5Gbps Type-A           AUDIO PORTS         1 x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 3W           VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         30.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 24	VIEWING ANGLE	178°(H) / 178°(V)
CONTRAST RATIO       3500:1         ADOBE RGB / DCI-P3 / SRGB       92% / 95% /119%         ACTIVE DISPLAY AREA (MM)       797.22 (H) x 333.72 (V)         PIXEL PITCH (H X V)       0.23175 (H) x 0.23175 (V)         SURFACE TREATMENT       Anti-Glare         DISPLAY COLORS       1.07B         COLOR BIT       10 bits (8bits + FRC)         HDR Ready       2x HDMI™ 2.0b (UWQHD@100Hz)         VIDEO PORTS       1x USB 5Gbps Type-B         1x USB 5Gbps Type-B       2x USB 5Gbps Type-B         2x USB 5Gbps Type-B       2x USB 5Gbps Type-A         AUDIO PORTS       1 x Headphone-out         KENSINGTON LOCK       Yes         SPEAKER       2x 3W         VESA MOUNTING       75 x 75 mm         POWER TYPE       External Adaptor 19V 9.47A         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE       AMD FreeSync™ Premium         TECHNOLOGY       ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ASPECT RATIO	21:9
ADOBE RGB / DCI-P3 / SRGB  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  VIDEO PORTS  USB Ports  AUDIO PORTS  AUDIO PORTS  EN 1 x Headphone-out  KENSINGTON LOCK  SPEAKER  VESA MOUNTING  POWER TYPE  POWER INPUT  DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  PIXEL PITCH (H X V)  1.0 23175 (H) x 0.23175 (V)  Anti-Glare  1.0.7B  1.0 bits (8bits + FRC)  HDR Ready  2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD  1x USB 5Gbps Type-B 2x USB 5Gbps Type-B 2x USB 5Gbps Type-A  1x Headphone-out  KENSINGTON LOCK  Yes  POWER TYPE  External Adaptor 19V 9.47A  AMD FreeSync™ Premium  308.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)  CARTON DIMENSION (W X H X D)	CURVATURE	1500R
ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  VIDEO PORTS  1.0 bits (8bits + FRC)  HDR Ready  2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD  USB Ports  AUDIO PORTS  1 x Headphone-out  KENSINGTON LOCK  SPEAKER  VESA MOUNTING  POWER TYPE  EXTERNAL Adaptor 19V 9.47A  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (SWIVEL)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  POSS 1.0 23175 (H) x 333.72 (V) 0.23175 (H) x 0.23175	CONTRAST RATIO	3500:1
PIXEL PITCH (H X V)         0.23175 (H) x 0.23175 (V)           SURFACE TREATMENT         Anti-Glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8bits + FRC)           HDR Ready         2x HDMI™ 2.0b (UWQHD@100Hz)           VIDEO PORTS         1x DisplayPort 1.4a           1x Type-C (DP Alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B           2x USB 5Gbps Type-A           AUDIO PORTS         1 x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 3W           VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ADOBE RGB / DCI-P3 / SRGB	92% / 95% /119%
SURFACE TREATMENT DISPLAY COLORS 1.07B  COLOR BIT 10 bits (8bits + FRC)  HDR Ready  2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD  USB Ports 1x USB 5Gbps Type-B 2x USB 5Gbps Type-A  AUDIO PORTS 1 x Headphone-out  KENSINGTON LOCK Yes  SPEAKER 2x 3W  VESA MOUNTING 75 x 75 mm  POWER TYPE External Adaptor 19V 9.47A  POWER INPUT 100~240V, 50~60Hz  DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  40 bits (8bits + FRC) 10 cbits (8bits + FRC) 10 bits (8bits + FRC) 10 cbits (8bits + FRC) 10 bits (8bits + FRC) 14 bits (2 bits (4 A) bits (2 bits (4 A)	ACTIVE DISPLAY AREA (MM)	797.22 (H) x 333.72 (V)
DISPLAY COLORS   1.07B   10 bits (8bits + FRC)	PIXEL PITCH (H X V)	0.23175 (H) x 0.23175 (V)
COLOR BIT HDR SUPPORT HDR Ready  2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD  USB Ports 1x USB 5Gbps Type-B 2x USB 5Gbps Type-A  AUDIO PORTS 1 x Headphone-out  KENSINGTON LOCK Yes  SPEAKER 2x 3W  VESA MOUNTING 75 x 75 mm  POWER TYPE External Adaptor 19V 9.47A  POWER INPUT 100~240V, 50~60Hz  DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  PX HDMI™ 2.0b (UWQHD@100Hz) 1x UsB port 2x USB 5Gbps Type-B 2x USB 5	SURFACE TREATMENT	Anti-Glare
HDR SUPPORT         HDR Ready           VIDEO PORTS         2x HDMI™ 2.0b (UWQHD@100Hz)           1x DisplayPort 1.4a         1x Type-C (DP Alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B           AUDIO PORTS         1 x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 3W           VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	DISPLAY COLORS	1.07B
VIDEO PORTS       2x HDMI™ 2.0b (UWQHD@100Hz)         1x DisplayPort 1.4a       1x Type-C (DP Alt.) w/ 98W PD         USB Ports       1x USB 5Gbps Type-B         2x USB 5Gbps Type-A       2x USB 5Gbps Type-A         AUDIO PORTS       1 x Headphone-out         KENSINGTON LOCK       Yes         SPEAKER       2x 3W         VESA MOUNTING       75 x 75 mm         POWER TYPE       External Adaptor 19V 9.47A         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	COLOR BIT	10 bits (8bits + FRC)
VIDEO PORTS       1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD         USB Ports       1x USB 5Gbps Type-B 2x USB 5Gbps Type-A         AUDIO PORTS       1 x Headphone-out         KENSINGTON LOCK       Yes         SPEAKER       2x 3W         VESA MOUNTING       75 x 75 mm         POWER TYPE       External Adaptor 19V 9.47A         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	HDR SUPPORT	HDR Ready
QX USB 5Gpps Type-A           AUDIO PORTS         1 x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 3W           VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	VIDEO PORTS	1x DisplayPort 1.4a
KENSINGTON LOCK       Yes         SPEAKER       2x 3W         VESA MOUNTING       75 x 75 mm         POWER TYPE       External Adaptor 19V 9.47A         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	USB Ports	
SPEAKER         2x 3W           VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	AUDIO PORTS	1 x Headphone-out
VESA MOUNTING         75 x 75 mm           POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	KENSINGTON LOCK	Yes
POWER TYPE         External Adaptor 19V 9.47A           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™ Premium           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -30° ~ 30°           ADJUSTMENT (PIVOT)         -5° ~ 5°           ADJUSTMENT (HEIGHT)         0 ~ 110 mm           DIMENSION (W X H X D)         808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)           CARTON DIMENSION (W X H X D)         945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	SPEAKER	2x 3W
POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	VESA MOUNTING	75 x 75 mm
DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	POWER TYPE	External Adaptor 19V 9.47A
TECHNOLOGY       AMD FreeSync ™ Premium         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (SWIVEL)       -30° ~ 30°         ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	POWER INPUT	100~240V, 50~60Hz
ADJUSTMENT (SWIVEL) $-30^{\circ} \sim 30^{\circ}$ ADJUSTMENT (PIVOT) $-5^{\circ} \sim 5^{\circ}$ ADJUSTMENT (HEIGHT) $0 \sim 110 \text{ mm}$ DIMENSION (W X H X D) $808.6 \times 424.1 \times 250.6 \text{ mm}$ (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D) $945 \times 510 \times 245 \text{ mm}$ (37.2 x 20.1 x 9.7 inch)		AMD FreeSync™ Premium
ADJUSTMENT (PIVOT)       -5° ~ 5°         ADJUSTMENT (HEIGHT)       0 ~ 110 mm         DIMENSION (W X H X D)       808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)         CARTON DIMENSION (W X H X D)       945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ADJUSTMENT (TILT)	-5° ~ 20°
ADJUSTMENT (HEIGHT) 0 ~ 110 mm  DIMENSION (W X H X D) 808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)  CARTON DIMENSION (W X H X D) 945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ADJUSTMENT (SWIVEL)	-30° ~ 30°
DIMENSION (W X H X D)          808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)          CARTON DIMENSION (W X H X D)          945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ADJUSTMENT (PIVOT)	-5° ~ 5°
CARTON DIMENSION (W X H X D) (31.83 x 16.70 x 9.87 inch)  945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)	ADJUSTMENT (HEIGHT)	0 ~ 110 mm
(37.2 x 20.1 x 9.7 inch)	DIMENSION (W X H X D)	
WEIGHT (NW / GW) 8.05 kg (17.81 lbs) / 11.9 kg (26.23 lbs)	CARTON DIMENSION (W X H X D)	
	WEIGHT (NW / GW)	8.05 kg (17.81 lbs) / 11.9 kg (26.23 lbs)

#### **FEATURES**

#### **UWQHD (3440 x 1440)**

UWQHD

Game titles will even look better, displaying more details due to the WQHD (3440 x 1440) resolution.



#### Curved 1500R

**1500R** Bring an immersive & comfortable viewing experience to eliminate distortion and cover a wider field of view



## 120Hz High Refresh Rate

120 Hz Enjoy the high-quality entertainment with a smoother and flicker-



#### Type C Display

Allows you to connect the latest devices more conveniently and with less trouble.



## **KVM Function Support**

Control multiple devices via one set of keyboard, mouse, and MSI monitor.



#### PIP / PBP Mode

PIP/PBP mode provide a better efficiency for creators when need it



## EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



#### **Built-In Speaker**

Built-in speakers allow you to listen clearly without connecting external speakers.



# **Modern MD342CQPW**

BE YOUR WINDOW TO THE WORLD

CERTIFICATES	CB/CE, Energy Star
VIDEO INPUT COMPATIBILITY	PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook *All trademarks and the registered trademarks are the property of their respective owners.
ACCESSORIES	1x DisplayPort 1.2a cable, 1x USB 3.2 Gen 1 Type-B to A cable, 1x Power Adaptor, 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screws
Note	HDMI™: 3440 x 1440 (Up to 100Hz) DisplayPort: 3440 x 1440 (Up to 120Hz) Type-C: 3440 x 1440 (Up to 120Hz) HDMI™ CEC Support Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard

# **CONNECTIONS**



- 1. 1x DC Jack
- 2. 1x Headphone-out
- 3. 2x HDMI 2.0b
- 4. 1x DisplayPort 1.4a
- 5. 1x Type-C (DP Alt.) w/ 98W PD
- 6. 1x USB 5Gbps Type-B
- 7. 2x USB 5Gbps Type-A
- 8. 1x Kensington Lock
- 9. OSD Button