

Technical Data Sheet

CODE 40316

**E 504 T ATEX GR II CAT 2G/D
B T4/135 X**

Direct Drivan cabinet fans for installation
in potentially explosive areas



Certifications


CE ATEX-CE



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,64	Number of speeds	1
Absorbed Power max (W)	293	Voltage (V)	400
Frequency (Hz)	50	Weight (Kg)	13,6
Insulation Class	I°	Delivery max (l/s)	1361,1
IP	65	Delivery max (m³/h)	4900
Max ambient temperature for continuous operation (°C)	+ 40	Pressure max (mmH2O)	17,7
Min ambient temperature for continuous operation (°C)	- 20	Pressure max (Pa)	173,8
Number of Phases (Ph)	3	RPM	1400
Number of Poles	4	Sound Pressure level Lp [dB (A)] 3m	72,7

DIMENSIONS



Diametro Ø (mm)	500
Etichetta Energetica	N0
Size A (mm)	630
Size B (mm)	630
Size C (mm)	325
Size D (mm)	530
Size E (mm)	510
Size F (mm)	498
Size G (mm)	112
Size H (mm)	12
Size L (mm)	15
Size M (mm)	528
Size N (mm)	518

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 40316

**E 504 T ATEX GR II CAT 2G/D
B T4/135 X**



Direct Driven cabinet fans for installation
in potentially explosive areas

DESCRIPTION

- Nominal diameter 500 mm
- Frame with port and grille made of pressed steel, pickled and phosphated, and treated initially with epoxy base coat; thereafter, grey textured finish obtained by applying a coat of polyurethane powder paint strengthened by oven baking.
- 1 speed asynchronous three-phase AC motor with shaft turning in double shielded ball bearings, size to UNEL MEC standard, flange B35, manufactured employing methods and materials suitable for use in environments with potentially explosive atmospheres, according to Explosion Protection standards EN 60079-0; EN 60079-7; EN 61241-0; EN 61241-1.
- Maximum air flow 4,900 m³/h
- Impeller with aluminium hub and blades of antistatic nylon filled with glass fibre.
- Aluminium cooling fan.
- Pressed steel motor cover.
- Metal cable glands for electrical connection.
- IMQ-certified for use in areas at risk of explosion due to presence of gas and dust:
 - o IMQ 10 ATEX 029 X; GR II cat. 2G/2D b T4/135 X

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com