

# Technical Data Sheet

CODE 25045

## DEPURO 45 H

Air cleaners with HEPA filter




### Certifications



### TECHNICAL AND PERFORMANCE DATA

|                          |      |                                                 |      |
|--------------------------|------|-------------------------------------------------|------|
| Absorbed Current max (A) | 0,27 | Delivery 1st speed (m <sup>3</sup> /h)          | 30   |
| Absorbed Power max (W)   | 30   | Max delivery at max speed (m <sup>3</sup> /h)   | 60   |
| Frequency (Hz)           | 50   | Sound power Lw [dB(A)] - min speed              | 41   |
| Insulation Class         | II°  | Sound power Lw [dB(A)] - max speed              | 53   |
| Number of speeds         | 3    | Sound power Lw [dB(A)] - mid speed              | 50   |
| Voltage (V)              | 230  | Sound pressure level Lp [dB (A)] 3m - max speed | 39,1 |
| Weight (Kg)              | 4,0  | Sound pressure level Lp [dB (A)] 3m - mid speed | 35,7 |
|                          |      | Sound pressure level Lp [dB (A)] 3m - min speed | 27,5 |

### DIMENSIONS



|                      |     |
|----------------------|-----|
| Etichetta Energetica | NO  |
| Size A (mm)          | 358 |
| Size B (mm)          | 180 |
| Size C (mm)          | 437 |
| Size D (mm)          | 315 |
| Size E (mm)          | 120 |

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

# Technical Data Sheet

CODE 25045

## DEPURO 45 H

Air cleaners with HEPA filter



---

### DESCRIPTION

- Upper casing, filter cover, sides, grille and base moulded from impact-resistant thermoplastic material, colour grey.
- 3 speed motor with thermal overload protection and double extension shaft turning in self-lubricating bushings, coupled to 2 impellers made of thermoplastic material; vibration eliminated by rubber dampers located between motor and mounting.
- Washable polyester-polyurethane prefilter.
- HEPA H10 filter
- Electrostatic double layer filter impregnated with activated carbon.
- Ionizing electrodes selectable by way of dedicated switch.
- On/off switch.
- Fan speed controlled by 3-position rotary switch.
- Base interchangeable with one side to allow floor-standing operation.
- Power cord with moulded plug.
- IMQ safety certification.

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: [prevendita@vortice-italy.com](mailto:prevendita@vortice-italy.com)