

## TP-Link LS1005G network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

**Brand :** TP-Link

**Product code:** LS1005G

**Product name :** LS1005G



- 5 x 10/100/1000Mbos Auto-Negotiation RJ45 port, supporting Auto-MDI/MDIX

- Green Ethernet technology saves power

- IEEE 802.3X flow control provides reliable data transfer

- Plastic casing, desktop or wall-mounting design

- Plug and play, no configuration needed

- Fanless design ensures quiet operation

LS1005G, IEEE 802.3i/802.3u/ 802.3ab/802.3x, 5x 1G RJ-45, 10 Gbps, 7.4 Mpps, 90x72x23 mm  
 TP-Link LS1005G. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 5 V. Wall mountable



### Management features

Switch type \* Unmanaged

### Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity \* 5

Basic switching RJ-45 Ethernet ports type \* Gigabit Ethernet (10/100/1000)

### Network

Networking standards \* IEEE 802.3i, IEEE 802.3u, IEEE 802.3x

10G support \* ✗

Flow control support ✓

Auto MDI/MDI-X ✓

Auto-negotiation ✓

### Data transmission

Switching capacity \* 10 Gbit/s

Forwarding rate 7.4 Mpps

MAC address table \* 2000 entries

Store-and-forward ✓

Jumbo frames support ✓

Jumbo frames 16000

Packet buffer memory 1.5 MB

### Design

Rack mounting \* ✗

Product colour Black

Housing material Plastic

LED indicators ✓

### Design

International Protection (IP) code IP20, IP40

Wall mountable ✓

Certification CE, FCC, RoHS

### Power

Power supply included \* ✓

DC input voltage 5 V

Input current 0.6 A

Power consumption (max) 3.7 W

### Power over Ethernet (PoE)

Power over Ethernet (PoE) \* ✗

### Operational conditions

Operating temperature (T-T) 0 - 40 °C

Storage temperature (T-T) -40 - 70 °C

Operating relative humidity (H-H) 10 - 90%

Storage relative humidity (H-H) 5 - 90%

Heat dissipation 12.617 BTU/h

### Weight & dimensions

Width 90 mm

Depth 72 mm

Height 23 mm


### Packaging data

Quick start guide ✓

Package type Box

### Logistics data

Harmonized System (HS) code 85176990



845973085469

0845973085469

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.