



IN-COUNTER SCANNER



1. IP54 rigid frame & EAS compatible
2. Large window & sharp LED indicator
3. Multi-interface support & back mounting holes

GST-688

Compact Dual-Laser Omnidirectional Vertical Scanner

The GST-688 vertical scanner's dual-laser technology uses two laser diodes which scan in 8 directions at once, enabling 32 scan lines at a rate of 2,400 scans per second. A top performer built for high-volume application, the GST-688 with proprietary hardware decoding technology delivers ultimate scanning performance from a vertical stance. The GST-688 comes in a rugged, cubical, aluminum dye-cast housing, meeting IP54 standards for protection against splashed water and dust.

- Instant "object-fly-by" automatic wake-up
- EAS compatible
- Strict IP54 standards
- Barcode stitching capable



OPERATIONAL

Light Source	Dual 650 nm visible laser diodes (VLD)
--------------	--

5 mil: 0 – 60 mm
7.5 mil: 0 – 150 mm
10 mil: 0 – 180 mm
13 mil: 0 – 220 mm
20 mil: 0 – 300 mm

Scan Line	32
-----------	----

Scan Rate	2,400 scans per second
-----------	------------------------

Scan Pattern	8 directions of scan field
--------------	----------------------------

Print Contrast	30% @ UPC/EAN 100%
----------------	--------------------

Indicator	Two-color LED (blue & red)
-----------	----------------------------

Beeper Operation	Programmable tone & beep time
------------------	-------------------------------

System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, wand
------------------	--

PHYSICAL

Dimension	152.0 x 152.0 x 82.0 mm
-----------	-------------------------

Weight	1,200 g
--------	---------

Cable	Standard 2M straight
-------	----------------------

POWER

Input Voltage	5 VDC ±10%
---------------	------------

Power Consumption	1.5 watts
-------------------	-----------

Operating Current	300 mA
-------------------	--------

REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
-------------	--------------------------------------

EMC	CE & FCC DOC compliance, BSMI
-----	-------------------------------

ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
-----------------------	---------------------------

Storage Temperature	-20°C – 60°C (-4°F – 140°F)
---------------------	-----------------------------

Humidity	5% – 95% RH (non-condensing)
----------	------------------------------

Light Level	Max. 4,500 Lux (fluorescence)
-------------	-------------------------------

Drop Durability	Designed to withstand 1M drops
-----------------	--------------------------------

Compatibility	EAS compatible
---------------	----------------

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded
------------	--

