



|                        |                                  |                               |              |
|------------------------|----------------------------------|-------------------------------|--------------|
| <b>EAN:</b>            | 4013288170125                    | <b>Size:</b>                  | 150x80x30 mm |
| <b>Part number:</b>    | 05073599001                      | <b>Weight:</b>                | 242 g        |
| <b>Article number:</b> | 967/9 TX B0 Multicolour 1 SB SiS | <b>Country of origin:</b>     | CZ           |
|                        |                                  | <b>Customs tariff number:</b> | 82041100     |

- L-keys for TORX® B0 screws to loosen safety connections
- Colour coded, easy-to-grip plastic sleeve, even at low temperatures
- BlackLaser tempered offers optimum surface protection for a long service life
- The ballpoint allows offset working
- Wear-resistant inscription of the sizes of the L-keys contained on the clip

L-keys with thermoplastic sleeve (SPKL) out of easy-to-grip circular material. The sleeve ensures that work is pleasant and easy on the fingers even at low temperatures. All L-keys are quickly to hand thanks to their colour coding and size markings. The wear-resistant clip material ensures secure storage of the L-keys as well as simple removal. For TORX® and TORX® B0 (with bore hole) connections.

**Web link**  
<https://www.wera.de/en/05073599001>

Wera - 967/9 TX B0 Multicolour 1 SB SiS  
05073599001 - 4013288170125

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

#### TORX® with borehole (B0)



L-key for TORX® socket screws with safety pin



TORX® tools with a borehole prevent the unauthorised unfastening of safety screws. The screws contain a pin that protrudes into the drive profile so that "normal" TORX® tools cannot be used. This pin fits into the borehole of TORX® B0 tools allowing safety screws to be unfastened.

#### TORX® ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

#### Magnetiser/Demagnetiser



For recessed screws, it's often advantageous for the screw to be held on the L-key by magnetic force. The Wera clips with magnetiser/demagnetiser enable a magnetisation/demagnetisation of L-keys in a flash.

#### Magnetising



#### Demagnetising



#### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

#### Secure hold and easy removal



The wear-resistant clip material ensures that the L-keys are securely held yet are easy to remove.

#### Web link

<https://www.wera.de/en/05073599001>

Wera - 967/9 TX B0 Multicolour 1 SB SiS  
05073599001 - 4013288170125

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**967/9 TX B0 Multicolour 1 SB L-key set for tamper-proof TORX® screws,  
BlackLaser, 9 pieces**



**Set contents:**

**967 SPKL TORX® B0 L-key Multicolour, TX 9 x 79 mm**



|                           |    |                |
|---------------------------|----|----------------|
| 05024351001 <sup>1)</sup> | 1x | TX 9 x 79 mm   |
| 05024350001 <sup>1)</sup> | 1x | TX 8 x 76 mm   |
| 05024352001 <sup>2)</sup> | 1x | TX 10 x 85 mm  |
| 05024353001               | 1x | TX 15 x 90 mm  |
| 05024354001               | 1x | TX 20 x 96 mm  |
| 05024355001               | 1x | TX 25 x 104 mm |
| 05024357001               | 1x | TX 30 x 122 mm |
| 05024358001               | 1x | TX 40 x 132 mm |
| 05024356001               | 1x | TX 27 x 112 mm |

1) Product without bore hole at the short and without ball-end at the long arm.

2) Product without ball-end at the long arm.

**Web link**

<https://www.wera.de/en/05073599001>

Wera - 967/9 TX B0 Multicolour 1 SB SiS  
05073599001 - 4013288170125

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)