

# MIG200 (N2K2)

## Accessories

- 3M 15AK MIG torch
- 2.5M earth clamp: 300A-16mm<sup>2</sup>
- 1 pc Euro quick connector

## Features

- Multi-function capability: supports MIG, Lift TIG, MMA, and FCAW-S
- User-friendly interface with pre-set current and voltage display for easy operation
- Fully digital control for precise and intelligent welding
- Built-in hot start, arc force, and anti-stick
- 2T/4T functionality; Adjustable inductance
- Unique air passage and dust-proof design for efficient cooling and reliable performance in harsh environments
- VRD (Voltage Reduction Device) for enhanced safety in high-risk environments
- Comprehensive protection system against overcurrent, overheating, and undervoltage



## Specifications

| Model                       | MIG200(N2K2)          |
|-----------------------------|-----------------------|
| Rated Input Power Source    | AC230V±15% 50/60Hz    |
| Rated Input Power           | 7.4 kVA               |
| Open Circuit Voltage        | 62 V                  |
| Welding Current Range (MIG) | 50-180 A/ 11.0-26.0 V |
| Welding Current Range (TIG) | 20-180 A              |
| Welding Current Range (MMA) | 20-160 A              |
| Wire Feed Speed             | 2.0-16.0 m/min        |
| Hot Start (Built-in)        | 60 A                  |
| Arc Force (Built-in)        | 60 A                  |
| Rated Duty Cycle (40°C)     | 20%                   |
| Overall Efficiency          | 80%                   |
| Power Factor                | 0.7                   |
| Protection Class            | IP21S                 |
| Insulation Class            | H                     |
| Compliance Standard         | IEC 60974-1           |
| Net Weight                  | 9 kg                  |
| Dimensions(L*W*H)           | 438*212*315 mm        |