

אל פסק 3.9 TOP Vision

תכונות

- און ליין המרה כפולה
- תוכנה לשליטה ובקרה מרחוק
- מטען חכם להארכת חיי אורך המצבר ועילותו
- מתקן מקדם הספק בכניסה 0.99
- בורר תדר אוטומטי 50/60Hz
- מפסק כיבוי בחרום
- תוכנה להורדה של Win/Linux ברשת- מממשק RS232 / USB
- מוד חיסכון בחשמל
- חייווי זמן גיבוי גם בעת חיבור מארז מצברים נוסף
- צד דיגיטאלי, ידידותי, נוח וקל לשימוש
- הגנות בפני ספייקים 600 ג'אול
- מארז מצברים חם לשליפה



Specifications

Model		Top Vision 3.9K
Input		
Capacity		3900VA / 2700W
Voltage Range	Low line Transfer	160VAC / 140VAC / 120VAC / 110VAC ± 5% (based on load percentage 100%-80% / 80%-70% / 70%-60% / 60%-0)
	Low Line Comeback	170 VAC / 150 VAC /130 VAC /120 VAC
	High line Transfer	300 VAC ±5 VAC
	High Line Comeback	290 VAC ±5 VAC
Frequency range		45Hz ~ 55Hz or 56Hz ~ 65Hz
Phase		Single phase with ground
Power factor		≥0.99 @ nominal voltage (100% load)
Output		
AC voltage regulation (Batt.mode)		± 1%
Frequency range (Synchronized range)		48 ~ 52 Hz or 58 ~ 62Hz
Frequency range (Batt.mode)		50 Hz ± 0.2 Hz or 60Hz ± 0.5Hz
Current crest ratio		3:1
Harmonic distortion		≤ 2% THD (linear load); ≤ 8% THD (non linear load)
Transfer time	Line mode to battery mode	Zero
	Inverter to bypass	Zero
Spike protection		600 Joules
Waveform (Batt. Mode)		Pure sine wave
Efficiency		
AC mode		88%
Battery mode		85%
Battery		
Standard model	Battery type	12V /9 AH
	Typical recharge time	5 hours recover to 90% capacity
	Charging current (max.)	1.0 A
	Charging voltage	82.2 VDC ± 1%
Indicators		
LCD displays		Load level, battery level, AC mode, battery mode, bypass mode and fault indicator
Alarm		
Battery mode		Sounding every 4 seconds
Low battery		Sounding every second
Overload		Sounding twice every second
Fault		Continuously sounding
Physical		
Standard model	Dimensions DxWxH (mm)	600 x 438 x 88
	Net weight (kgs)	28
Environment		
Humidity		20-90 % RH @ 0-40 °C (non condensing)
Working Temp		0-40°C
Noise level		Less than 50dBA @ 1 meter
Management		
Smart RS-232		Support windows 2000/2003/XP/Vista/2008/7, Linux, Mac and Solaris 8,9,10
Optional USB		
Optional SNMP		Power management from SNMP manager and web browser
Dry contact		Dry contact card optional
Standards		CE, EN62040-1 (Safety), EN62040-2 (EMC)

* Product specifications are subject to change without further notice