FASTENING

IMPACT WRENCH COMPOSITE

Bolt Capacity 16mm

● Lightweight. ● Reverse lever.

SP-7143

1/2" Retainer ring

④ Regulator dial



Bolt Capacity 16mm

● Lightweight. ● Reverse lever.

SP-7143DX

1/2" Retainer ring

④ Regulator lever



Bolt Capacity 14mm

● Lightweight. ● Reverse lever.

SP-7142S

3/8" Retainer ring

④ Regulator dial



Bolt Capacity 16mm

● Lightweight. ● Reverse lever.

SP-7140

1/2" Retainer ring

④ Regulator dial



Bolt Capacity 25mm

● One hand reverse button (patented).

SP-7150A-V8

3/4" Retainer ring

④ Regulator dial



Bolt Capacity 25mm

● One hand reverse button (patented).

SP-7151AL-V8

3/4" Retainer ring

④ Regulator dial



Option

● #26061990 Support grip

Bolt Capacity 32mm

● Lightweight. ● One hand reverse button (patented).

SP-7191A-V8

1" Retainer ring

④ Regulator dial



Option

● #26061990 Support grip

EDP	Model No.	Sq. Drive (inch)	Hammer	Torque Range (N·m)	Free Speed (min^{-1})	Overall Length (mm)	Air Consumption (m^3/min)	Hose Coupling	Net Weight (kg)	JAN (4545695)
370021	**SP-7143**	1/2"	Dyna Jaw clutch	50~280	8000	180	0.6	1/4"NPT	1.36	000165
370028	**SP-7143DX**	1/2"	Dyna Jaw clutch	50~320	8000	173	0.6	1/4"NPT	1.36	001629
370187	**SP-7142S**	3/8"	Twin Dog clutch	50~270	7500	163	0.4	1/4"NPT	1.4	001049
370032	**SP-7140**	1/2"	Twin dog clutch	50~450	5800	185	0.6	1/4"NPT	2.1	000158
370029	**SP-7150A-V8**	3/4"	Twin Dog clutch	300~1000	4300	237	1.3	3/8"NPT	3.7	002572
370041	**SP-7151AL-V8**	3/4"	Pin clutch	270~900	4300	320	0.8	3/8"NPT	4.5	002503
370042	**SP-7191A-V8**	1"	Pin clutch	280~1100	4300	320	0.8	1/2"NPT	4.65	002602

Air pressure: 0.62 MPa Air hose inner dia.: 9.5 mm Rear exhaust Air connector included