



רוק פתרונות טכניים בע"מ



Specifications	Range	Best Accuracy
Model		UT33D
DC Voltage (V)	200mV/2000mV/20V/200V/500V	$\pm(0.5\%+2)$
AC Voltage (V)	200V/500V	$\pm(1.2\%+10)$
DC Current (A)	2000 μ A/20mA/200mA/10A	$\pm(1\%+2)$
Resistance (Ω)	200 Ω /2000 Ω /20k Ω /200k Ω /20M Ω /200M Ω	$\pm(0.8\%+2)$
Features		
Display Count		2000
Manual Range		√
Square Wave Output		√
Diode		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
LCD Backlight		√
Input Impedance for DCV	Around 10M Ω	√
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	48mm×16mm	
Product Color	Red and Grey	
Product Net Weight	179g (Including Holster)	
Product Size	130mm×73.5mm×35mm	
Standard Accessories	Battery, Test Lead,Holster	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	60 PCs	
Standard Carton Measurement	490mm×356mm×315mm (0.055 CBM Per Standard Carton)	

רחוב כורזין 5 גבעתיים 5358305
טלפון 03-5712220 פקס 03-5734128
oshrat@rpt.co.il shai@rpt.co.il
WWW.RPT.CO.IL



Standard Carton Gross Weight	18Kg
------------------------------	------