

Specifications	Range	Best Accuracy
Model		UT201
AC Current (A)	2A/20A/200A/400A	$\pm(1.5\%+5)$
AC Voltage (V)	2V/20V/200V/600V	$\pm(1.2\%+5)$
DC Voltage (V)	200mV/2V/20V/200V/600V	$\pm(0.8\%+1)$
Resistance (Ω)	200 Ω /2K Ω /20K Ω /200K Ω /2M Ω /20M Ω	$\pm(1\%+2)$
Features		
Display Count		2000
Auto Range		√
Jaw Capacity		28mm
Diode		√
Auto Power Off		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
MAX Mode		√
Full Icon Display		√
Input Impedance for DCV	Around 10M Ω	√
General Characteristic		
Power	1.5V Batteries (R03) ×2	
LCD Size	35.6mm X 18 mm	
Product Color	Red and Grey	
Product Net Weight	220g	
Product Size	210mm X 75.6mm X30 mm	
Standard Accessories	Batteries, Test Lead, Carrying Bag	
Standard Individual Packing	Gift Box, English Manual	



Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)
Standard Carton Gross Weight	23Kg