

Specifications	Range	Best Accuracy
Model		UT33A
DC Voltage (V)	400mV/4V/40V/400V/500V	$\pm(0.8\%+1)$
AC Voltage (V)	4V/40V/400V/500V	$\pm(1.2\%+3)$
DC Current (A)	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1\%+2)$
AC Current (A)	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1.5\%+5)$
Resistance (Ω)	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Features		
Display Count		4000
Auto Range		√
Diode		√
Transistor		√
Continuity Buzzer		√
Low Battery Indication		√
Input Impedance for DCV	Around 10M Ω	√
General Characteristic		
Power	1.5V Batteries (R03)×2	
LCD Size	48mm×16mm	
Product Color	Red and Grey	
Product Net Weight	179g (Including Holster)	
Product Size	130mm×73.5mm×35mm	
Standard Accessories	Batteries, Test Lead,Holster	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	60 PCs	
Standard Carton Measurement	490mm×356mm×315mm (0.055 CBM Per Standard Carton)	
Standard Carton Gross Weight	18Kg	