

Specifications	Range	Best Accuracy
Model		UT50A
DC Voltage (V)	200mV/2V/20V/200V/1000V	$\pm(0.5\%+1)$
AC Voltage (V)	200mV/2V/20V/200V/750V	$\pm(0.8\%+3)$
DC Current (A)	20mA/2mA/200mA/20A	$\pm(0.8\%+1)$
AC Current (A)	200mA/2mA/200mA/20A	$\pm(1\%+3)$
Resistance (Ω)	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω /200M Ω	$\pm(0.8\%+1)$
Capacitance (F)	2nF/20nF/2 μ F/100 μ F	$\pm(4\%+3)$
Features		
Full Icon Display		√
Diode		√
Continuity Buzzer		√
Low Battery Display		√
Input Impedance for DC Voltage Measurement	10M Ω	√
Data Hold		√
Display Backlight	Auto	√
Max. Display	1999	√
Auto Power Off		√
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	95mm×25mm	
Product Colour	Red and Grey	
Product Net Weight	275g	
Product Size	165mm×80mm×38.3mm	
Standard Accessories	Test Lead, Battery, Test Clip	



Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 Pcs
Standard Carton Measurement	588mm×408mm×326mm(0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	20kg
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)