

Specifications	Range	Best Accuracy
Model		UT202
AC Current (A)	2A/20A/200A/400A	$\pm(1.5\%+5)$
AC Voltage (V)	2V/20V/200V/600V	$\pm(1.2\%+5)$
DC Voltage (V)	200mV/2V/20V/200V/600V	$\pm(0.8\%+1)$
Resistance (Ω)	200 Ω /2K Ω /20K Ω /200K Ω /2M Ω /20M Ω	$\pm(1\%+2)$
Temperature ($^{\circ}\text{C}$)	-40 $^{\circ}\text{C}$ ~ 1000 $^{\circ}\text{C}$	$\pm(1\%+3)$
Temperature ($^{\circ}\text{F}$)	-40 $^{\circ}\text{F}$ ~ 1832 $^{\circ}\text{F}$	$\pm(1\%+6)$
Features		
Display Count		2000
Auto Range		√
Jaw Capacity		28mm
Diode		√
Auto Power Off		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
MAX Mode		√
Full Icon Display		√
Input Impedance for DCV	Around 10M Ω	√
General Characteristic		
Power	1.5V Batteries (R03) $\times 2$	
LCD Size	35.6mm X 18 mm	
Product Color	Red and Grey	
Product Net Weight	220g	
Product Size	210mm X 75.6mm X30 mm	
Standard Accessories	Battery, Test Lead, Carrying Bag, Point Contact Temperature	



רוק פתרונות טכניים בע"מ

	Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)
Standard Carton Gross Weight	23Kg

רחוב כורזין 5 גבעתיים 5358305
טלפון 03-5712220 פקס 03-5734128
oshrat@rpt.co.il shai@rpt.co.il
WWW.RPT.CO.IL