



רוק פתרונות טכניים בע"מ



Specifications	Range		Best Accuracy
Model			UT531
Insulation Resistance(Ω)	Test Voltage	500V/1000V	0%~10%
	500V	0.5MΩ~99.9MΩ	±(3%+5)
		100MΩ~500MΩ	±(3%+5)
	1000V	4.0MΩ~99.9MΩ	±(3%+5)
		100MΩ~600MΩ	±(3%+5)
	Short-Circuit Current	<2mA	√
Multimeter Specifications			
DC Voltage (V)	60mV/600mV/6V/60V/600V/1000V		±(0.09%+6)
AC Voltage (50Hz~1KHz)	6V/60V/600V/1000V		±(1%+3)
DC Current (A)	60mA/600mA		±(1.0%+2)
AC Current (50Hz~1KHz)	60mA/600mA		±(1.5%+2)
Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/40MΩ		±(0.9%+2)
Capacitance (F)	10nF/100nF/1μF/10μF/100μF		±(3%+5)
Frequency (Hz)	60Hz/600Hz/6KHz/60KHz/600KHz/1MHz		±(0.1%+3)
Features			
Display Count			6000
Auto Range			√
True RMS			√
Diode			√
Auto Power Off			√
Continuity Buzzer			√
Low Battery Indication			√
Data Hold			√
MAX/MIN			√

רחוב כורזין 5 גבעתיים 5358305
טלפון 03-5712220 פקס 03-5734128
oshrat@rpt.co.il shai@rpt.co.il
WWW.RPT.CO.IL

Data Logging		99
LCD Backlight		√
Full Icon Display		√
General Characteristic		
Power	1.5V Alkaline Batteries (LR6)×6	
LCD Size	81mm X 46mm	
Product Color	Red and Grey	
Product Net Weight	505g	
Product Size	96.7mm X 202.8mm X46 mm	
Standard Accessories	Batterise, Test Lead, Alligator Clip, Carrying Bag	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	20 pcs	
Standard Carton Measurement	460mm X 310mm X 368mm(0.053 CBM Per Standard Carton)	
Standard Carton Gross Weight	12Kg	