



רוק פתרונות טכניים בע"מ



Specifications	Range	Best Accuracy
Model		UT15C
LED AC/DC Voltage Indication (V)	12V	0~10V
	24V	17V±2V
	50V	35V±5V
	120V	80V±15V
	230V	165V±20V
	400V	300V±30V
	690V	510V±40V
Phase Rotation Test	Operating Voltage: 0V~690V	√
	Frequency : 50Hz~ 60Hz	
Single Lead(L2)Voltage Detection	Operating Voltage : 100V~690V	√
	Frequency: 50Hz~ 400Hz	
Continuity Test	Resistance: 0~400KΩ	√
	Beeper and LED light Indicator	
Polarity Detection	Positive & Negative	√
Features		
Water-Proof (IP65)		√
Auto Range		√
Work Light		√
Low Battery Indication	Short circuit two leads,LED and beeper off when the battery is low	√
LCD AC/DC Voltage Display	24V~ 690V	±(3%+8)
General Characteristic		
Power	1.5V Batteries (R03) X 2	
LCD Size	23 X 12mm	
Product Color	Red and Grey	
Product Net Weight	210g	

רחוב כורזין 5 גבעתיים 5358305
טלפון 03-5712220 פקס 03-5734128
oshrat@rpt.co.il shai@rpt.co.il
WWW.RPT.CO.IL



Product Size	275mm X 51mm X 30 mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	30PCs
Standard Carton Measurement	440mm×395mm×455mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	11.2Kg