

BioMini Plus 2

PIV Certified Authentication Scanner



| BioMini Plus 2 | Suprema BioMini Plus 2 has been designed to provide high level security solution with its proven reliability of FBI-PIV certification. BioMini Plus 2 features industry's most advanced MDR(multi dynamic range) technology to capture exceptional image quality even under extreme lighting conditions(operates under direct sunlight up to 100,000 LUX).

The scanner also features cutting-edge live fingerprint detection(LFD) technology for improved security against spoofing, and the latest version of multi award-winning Suprema algorithm for better performance. Combined with ergonomic design, high speed USB 2.0 interface and comprehensive SDK solution, BioMini Plus 2 offers superb biometric authentication solution for both public and commercial applications.



BioMini Plus 2

PIV Certified Authentication Scanner



FEATURES



- FBI PIV and FBI Mobile ID FAP10 certificates
- Image compression standard: WSQ



- Multi Dynamic Range (MDR) Technology
- Operates under direct sunlight up to 100,000 LUX



- Live Fingerprint Detection (LFD) Technology
- Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- New Improved Optical Sensor
- 500dpi optical fingerprint sensor
- Scratch proof IP65 sensor surface



- Easy Integration
- BioMini SDK for easy application development
- Android, MS Windows & Linux compatible
- Multi-threaded code design for multi-core CPU utilization

SPECIFICATIONS

	Image Quality Standards	FBI PIV/FIPS 201 FBI Mobile ID FAP10
Sensor	Live Finger Detection	O
	Sensor Type	Optical
	Resolution	500 ppi
	Gray Scale	256 level
	Platen Size (W x L mm)	16.0 x 19.0
	Sensing Area (W x H mm)	16.0 x 18.0
	Image Size (W x H pixels)	315 x 354
H/W	Interface	USB 2.0 High Speed
	Operating Temperature(°C)	-10~50°C
	Operating humidity	0 ~ 90% RH
	Ingress Protection	IP65 (Sensor Surface)
	Dimensions (W x L x H mm)	66 x 90 x 58
	Weight (g)	175
S/W	Windows	Windows XP, Vista, 7, 8, 8.1, 10 32/64bit
	Linux	Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit
	Android Android 4.1(Jelly Bean)and Above	O
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Suprema, ISO19794-2, ANSI-378
Certification	CE	O
	FCC	O
	KC	O
	RoHS	O
	UL	X
	USB-IF	O
	CB	O
	IEC62471(CB포함)	O
	WEEE	O
	REACH	X
	WHQL	O

Suprema ID Inc.

#305~308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea

Tel : +82-31-783-4502, Fax : +82-31-783-4503

E-mail : sales@supremainc.com Homepage : www.suprema-id.com

suprema
BIOMETRICS & SECURITY

©2020 Suprema, inc. Suprema and identifying product names and numbers herein are registered trade mark of Suprema, Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice. No representations or warranties, express or implied, are made as to, and no reliance should be placed on, the accuracy, fairness or completeness of the information presented or contained in this document. [DHL-BMP2-170417-02EN]