



## QNA-T310G1T

Interface	Single-port Thunderbolt 3 to single-port 10GbE NBASE-T RJ-45
Data Transfer	10Gbps; 5Gbps; 2.5Gbps; 1Gbps; 100Mbps
Cables	Thunderbolt 3: Thunderbolt 3 cable Network Cable: CAT 5e, CAT 6, CAT 6A, CAT 7 * 0.5M Thunderbolt3 40Gb/s cable x 1 included * Suggest using CAT 6 (or above) cable to achieve 10GbE transfer speed
Power Supply Unit	Bus powered
System Requirements (Windows)	Windows 7 (64-bit) / Windows 10 (64-bit) * Required download Aquantia <a href="#">AQC107S driver</a> * Required a Thunderbolt 3 port on your computer
System Requirements (Mac)	macOS 10.13.3 (or later) * Required a Thunderbolt 3 port on your computer
System Requirements (Linux)	Supports Linux core 3.10, 3.12, 3.2, 4.2, and 4.4. The driver for the Marvell AQtion AQC107 is required to use the QNA-T310G1T. <a href="#">Click here to download drivers</a>
System Requirements (QNAP NAS)	QNAP Thunderbolt 3 NAS (with QTS 4.3.6 or later) *Port trunking, DHCP/RADVD, and static route are not supported
Operating Temperature & Relative Humidity	100M CAT 6A: 35° 50M CAT 6A: 40° 5~95% (non-condensing)
Dimensions (H x W x D)	27.6 x 56 x 112 mm 1.08 x 2.20 x 4.41 inch
Weight	Net weight: 0.19Kg, Gross weight: 0.36Kg
LED Indicators	Power, LAN Link/Act, transfer speed
Package Contents	QNA-T310G1T, 0.5M Thunderbolt 3 cable x 1, installation guide