



LCD DISPLAY

VX2718-2KPC-MHD


Key Features

- 165Hz refresh rate delivers fluid, tear-free visuals
- Rapid 1ms (MPRT) response time for crisp movements
- QHD 1440p resolution
- 1500R curved screen for a perfect balance of immersion and comfort
- Flexible connectivity with dual HDMI and DisplayPort input



Product Description

With an immersive curved screen and 165Hz refresh rate, the ViewSonic VX2718-2KPC-MHD provides a stunning viewing experience. The monitor has been designed with a 1500R curved and borderless panel for an immersive experience. A high 165Hz refresh rate delivers smooth animations with minimal input lag while Adaptive Sync virtually eliminates screen tearing and stuttering for a fluid gaming experience. With 1ms MPRT response time, the monitor delivers unprecedented screen quality and speed. VX2718-2KPC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications, such as watching movies, editing, or playing video games. In addition, a DisplayPort and two HDMI inputs offer flexible connectivity for both general use and entertainment.



1. VESA Compatible(Wall Mount 100 x 100mm)
2. HDMI x 2
3. DP
4. Audio Out
5. DC In

Visit Us ■ www.viewsonic.com

DISPLAY		OPERATING CONDITIONS	
Display Size (in.):	27	Temperature:	32°F to 104°F (0°C to 40°C)
Viewable Area (in.):	27	Humidity (non-condensing):	20% to 90%
Panel Type:	VA Technology	WALL MOUNT	
Resolution:	2560 x 1440	VESA Compatible:	75 x 75 mm
Resolution Type:	QHD	INPUT SIGNAL	
Static Contrast Ratio:	4,000:1 (typ)	Frequency Horizontal:	HDMI (v2.0): 30 ~ 222KHz, DisplayPort (v1.2): 30 ~ 243KHz
Dynamic Contrast Ratio:	80M:1	Frequency Vertical:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.2): 48 ~ 165Hz
Light Source:	LED	VIDEO INPUT	
Brightness:	250 cd/m² (typ)	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)
Colors:	16.7M	ERGONOMICS	
Color Space Support:	8 bit (6 bit + FRC)	Tilt (Forward/Back):	-5° / 20°
Aspect Ratio:	16:9	WEIGHT (IMPERIAL)	
Response Time (MPRT):	1ms	Net (lbs):	8.6
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (lbs):	7.3
Backlight Life (Hours):	30000 Hrs (Min)	Gross (lbs):	12.1
Curvature:	1500R	WEIGHT (METRIC)	
Refresh Rate (Hz):	165	Net (kg):	3.9
Adaptive Sync:	Yes	Net Without Stand (kg):	3.3
Blue Light Filter:	Yes	Gross (kg):	5.5
Flicker-Free:	Yes	DIMENSIONS (IMPERIAL) (WXHxD)	
Color Gamut:	NTSC: 72% size (Typ), sRGB: 102% size (Typ)	Packaging (in.):	27 x 17.4 x 6.1
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Physical (in.):	24 x 18.7 x 8.8
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (in.):	24 x 14.3 x 2.9
COMPATIBILITY		DIMENSIONS (METRIC) (WXHxD)	
PC Resolution (max):	2560x1440	Packaging (mm):	687 x 443 x 156
Mac® Resolution (max):	2560x1440	Physical (mm):	611 x 475 x 225
PC Operating System:	Windows 10 certified; macOS tested	Physical Without Stand (mm):	611 x 363 x 75
Mac® Resolution (min):	2560x1440	GENERAL	
CONNECTOR		Regulations:	cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, BSMI, RCM, KC, e-Standby
3.5mm Audio Out:	1	PACKAGE CONTENTS:	
HDMI 2.0:	2	VX2718-2KPC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1	
Display Port:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Power in:	External power adapter	Warranty:	
AUDIO		*Warranty offered may differ from market to market	
Internal Speakers:	2Watts x2		
POWER			
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	External		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		