

Technical Data Sheet

CODE 61260

NORDIK 1S 120/48 SENZA GR.COM.

Ceiling fans with or without light




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,33	Airflow speed at max speed (m/s)	2,02
Absorbed Power max (W)	70	Delivery max (m³/h)	11820
Blades diameter	120	Delivery max (m³/min)	197,00
Frequency (Hz)	50	giri_minuto	205
Insulation Class	I°	RPM	205
Voltage (V)	220-240	Service value (m³/min)/W	2,814
Weight (Kg)	5,5	Sound power level Lw [dB(A)]	49,1

DIMENSIONS



Size A (mm)	Ø 1218
Size B (mm)	Ø 230
Size C (mm)	495

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 61260

NORDIK 1S 120/48 SENZA GR.COM.



Ceiling fans with or without light

DESCRIPTION

- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant PP, colour white.
- Nominal diameter of blades 1200 mm.
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings.
- Maximum air flow: 11,820 m³/h.
- 3 galvanized sheet steel blades powder coated with scratch-resistant polyester, colour white
- Steel ceiling rod with polyester powder coated finish, colour white, length 375 mm
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Speed selectable by way of control units or Telenordik 5T remote control (optional)

ACCESSORIES



SCNR5 UNIF.X NK SOFFITTO

Code 12955



KIT SCB5 (TRASF.5 V.)

Code 22483



KIT SCB (TRASF.E.C.)

Code 22481



TELENORDIK 5T

Code 22387



C 2.5 (COMANDO EL. 2.5 A)

Code 12967



SC 503 B

Code 12801



SC 503 N

Code 12802



SC EXT B

Code 12803



SCI503

Code 22461



PSC-W

Code 22462



PSC-B

Code 22463

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com



ASTA NK 200
BIANCA

Code 22030



ASTA NK 275
BIANCA

Code 22034



ASTA NK 350
BIANCA

Code 22040



ASTA NK 500
BIANCA

Code 22052



ASTA NK 750
BIANCA

Code 22072



ASTA NK 1000
BIANCA

Code 22075



SET PALE
120/48 DESIGN
BIANCO INT

Code 22642



VORT DELTA T

Code 13039

