



tesa® 60760

Product Information



Floor Marking Tape

Product Features

- Color combinations correspond to legally prescribed safety guidelines
- tesa®60760 has a flexible backing to cope with curves
- Durable and robust backing for floor marking applications; hand tearable
- Depending on its color, the floor-marking tape can be explicitly used as a warning tape.
- The modified natural rubber adhesive provides good adhesion to various surfaces.
- Thanks to the high degree of flexibility of the backing, it can also be used on rough surfaces and is also suitable for curved applications.

tesa® 60760 is a robust adhesive tape for moderate, temporary marking applications for e.g. mobile and stationary objects. The robust but still hand tearable floor-marking tape comprises a soft PVC backing with a modified natural rubber adhesive mass. tesa® 60760 is available in yellow, yellow/black, red, red/white, blue, green and white; the color combinations correspond to legally prescribed safety guidelines.

Application Fields

- tesa® 60760 is recommended for moderate, temporary marking for mobile and stationary object
- The floor marking tape can be used for marking of high-traffic areas, e.g. factories, warehouses, offices, or hospitals

Product Construction

- | | | | |
|--------------------|----------------|--------------------|----------|
| • Type of adhesive | natural rubber | • Backing material | soft PVC |
| • Total thickness | 150 µm | | |

Product Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-----------|
| • Elongation at break | 220 % | • Suitable for rough surfaces | very good |
| • Tensile strength | 33 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 2 N/cm |
|---------|--------|



tesa® 60760

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=60760>