

APC Easy UPS On-Line SRV RM 3000 VA 230V with Rail Kit

SRV3KRIRK

Call for More Information +61 2 9125 8951



- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: Basic UPS signalling RS-232 cable, CD with software, Rack Mounting brackets, Rack Mounting support rails, User Manual

Output

Output power capacity	2.4kWatts / 3.0kVA
Max Configurable Power (Watts)	2.4kWatts / 3.0kVA
Nominal Output Voltage	230V
Efficiency at Full Load	88.0 %
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Bypass	Internal Bypass (Automatic and Manual)

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC-320 C20
Cord Length	1.48meters
Input voltage range for main operations	160 - 280V
Input voltage adjustable range for mains operation	100 - 280 (half load)V
Number of Power Cords	1
Efficiency at Full Load	88.0 %
Other Input Voltages	220, 240

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4hour(s)
Battery Charge Power (Watts)	118Watts
Battery Volt-Amp-Hour Capacity	473
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	DB-9 RS-232, Smart-Slot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	--
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	600Joules

Physical	
Maximum Height	86MM, 8.6CM
Maximum Width	437MM, 43.7CM
Maximum Depth	632MM, 63.2CM
Rack Height	2U
Net Weight	27.6KG
Shipping weight	29.0KG
Shipping Height	229MM, 22.9CM
Shipping Width	569MM, 56.9CM
Shipping Depth	795MM, 79.5CM
Color	Black

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	50.0dBA
Protection Class	IP 20
Conformance	
Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.