



CX522

Reliability. Security. Productivity.



CX522



Lexmark CX522

The multifunction Lexmark CX522 builds on print speed up to 33 pages per minute* with a 10.9 cm colour touch screen. In addition to reliably handing diverse media types and sizes, it includes tools that help you both minimise toner consumption and get the colour right.



Ready when you are

- ▶ 1.2-GHz quad-core processor and up to 6 GB memory drives printing at up to 33 ppm*.
- ▶ Scan at up to 47 pages per minute.
- ▶ Steel frame and durable design stands up to heavy use and harsh environments.
- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 5000 colour and 8500 monochrome pages**.
- ▶ Keep printing in black even when colour toner is empty.

Colour that keeps saving

- ▶ PANTONE® calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- ▶ Save toner with suite of tools that let you choose when and how much colour to print.

Input that works

- ▶ Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- ▶ 251 pages of standard input can grow to 1451.

Interact with ease

- ▶ Tilttable 10.9 cm e-Task touch screen comes with convenience and productivity apps and is customisable to meet your needs.
- ▶ Front USB port allows walk-up printing from popular file formats without a computer.
- ▶ Compact footprint allows flexible placement in more locations.
- ▶ Connect easily via Ethernet, USB, or simple mobile printing options.

Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.
- ▶ Keypoint Intelligence - Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

**Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

***Award based on Western Europe data

Lexmark CX522



1 CX522 with 10.9-cm e-Task colour touch screen

462 x 442 x 588 mm

2 650-sheet duo tray

133 x 424 x 416 mm

3 550-sheet tray

133 x 424 x 416 mm

Adjustable printer stand (not shown)

521 x 653 x 625 mm

Swivel cabinet (not shown)

263 x 476 x 600 mm

 Standard

 Optional

Note 1: Supports one optional 650-sheet duo tray; or one optional 650-sheet duo tray and one optional 550-sheet tray with the 650-sheet duo tray on top.

Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2021 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE®, PANTONE® Goe™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

Product specifications		Lexmark CX522ade	Lexmark CX522de
Print			
Display		Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen	
Print Speed: Up to ⁶		Black: 33 ppm / Colour: 33 ppm	
Time to First Page: As fast as		Black: <8.5 seconds / Colour: <8.5 seconds	
Print Resolution		Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)	
Memory		Standard: 2048 MB / Maximum: 6144 MB	
Hard Disk		Option available	
Recommended Monthly Page Volume ²		1500 - 8500 pages	
Maximum Monthly Duty Cycle: Up to ³		85000 pages per month	
Copy			
Copy Speed: Up to ⁴		Black: 33 cpm / Colour: 33 cpm	
Time to First Copy: as fast as		Black: 9 seconds / Colour: 9.5 seconds	
Scan			
Scanner Type / ADF Scan		Flatbed scanner with ADF / RADF (reversing Duplex)	
A4/Ltr Duplex Scan Speed: Up to		Black: 21 / 23 sides per minute / Colour: 13 / 14 sides per minute	
A4/Ltr Simplex Scan Speed: Up to		Black: 47 / 50 sides per minute / Colour: 30 / 32 sides per minute	
ADF Paper Input Capacity: Up to		50 pages 75 gsm bond	
Fax			
Modem Speed		ITU T.30, V.34 Half-Duplex, 33.6 Kbps Kbps	
Supplies⁷			
Laser Cartridge Yields (up to) ¹		1,400-page Colour (CMY) Cartridges, 2,000-page Black Cartridge, 5,000-page Colour (CMY) Extra High Yield Cartridges, 8,500-page Black Extra High Yield Cartridge	
Photoconductor Estimated Yield: Up to ⁵		125000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage	
Cartridge(s) Shipping with Product ¹		2,000-page Colour (CMY) Return Program Toner Cartridges, 3,000-page Black Return Program Toner Cartridge	
Paper Handling			
Included Paper Handling		250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed	
Optional Paper Handling		550-Sheet Tray, 650-Sheet Duo Tray	
Paper Input Capacity: Up to		Standard: 250+1 pages 75 gsm bond / Maximum: 1450+1 pages 75 gsm bond	
Paper Output Capacity: Up to		Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond	
Media Types Supported		Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide	
Media Sizes Supported		10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Universal, Oficio, A6	
General Information⁴			
Standard Connectivity		USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A)	
Optional Network Ports		Marknet N8372 WiFi Option	
Noise Level: Operating		Print: 52 dBA / Copy: 56 dBA / Scan: 55 dBA	
Specified Operating Environment		Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)	
Product Guarantee		1-Year Onsite Repair, Next Business Day	1-Year Onsite Service, Next Business Day
Size (mm - H x W x D) / Weight		462 x 442 x 588 mm / 27.1 kg	

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ²Recommended Monthly Page Volume⁶ is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³Maximum Monthly Duty Cycle⁷ is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.