

tesa® Powerstrips Waterproof Duo Hook Plastic

BNR 59704, 59764

The self-adhesive tesa Powerstrips Waterproof Duo Hook is a removable and waterproof bathroom hook to hang up your shower wiper and body care utensils.

Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 3 kg
- Removable without a trace due to the Powerstrips® Waterproof technology
- Made from high quality plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- Ideal to hold a shower wiper but to be used as duo hook for sponges, towels, etc. as well
- Reusable with tesa Powerstrips Waterproof

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

Product Properties

• Applicationfield	Bathroom, Kitchen	• Solvent free	yes
• Type of tape	Double-sided adhesive	• Suitable surfaces	Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics
• Holding power up to	3 kg		
• UV-resistant	no		
• Water resistant	yes	• Reusable	yes
• Humidity resistant	yes	• Waterproof	yes
• Oil- and grease-resistant	no	• Hook shape	Rectangular
• Ozone resistant	yes	• Reusable with	Powerstrips Waterproof
• Resistance to chemicals	No	• Number of hooks	Double hook
		• Batteries required	no
		• Batteries included	no

Technical Data

• Application temperature	from 20°C up to 25°C	• Temperature resistant	yes
• Area of use	Indoor	• Temperature resistance from	15 °C
• Material	PS (polystyrol)	• Temperature resistance up to	35 °C
• Residue-free removable	yes	• Silicone free	yes
• Type of adhesive	synthetic rubber	• Hazard material	yes

Application

- How to apply - step-by-step:
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation - wait for 10 seconds minimum
 3. Apply the Powerstrip Waterproof Large strip on the surface - press for 5 seconds minimum

tesa® Powerstrips Waterproof Duo Hook Plastic

Application

4. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
5. Let the hook slide down on the base plate until it is locked

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.