

3 inch Rugged Mobile Printer **SPP-R300**

SPECIFICATIONS



Printer Specifications

Print Method

Direct Thermal Line Printing

Print Speed

Up to 100 mm/sec (Receipt)

Up to 80 mm/sec (Linerless)

12.5% pattern

Print Resolution

203 dpi

Print Width

Up to 72 mm

Sensor

Paper End: Reflective sensor

Paper Cover Open: Mechanical switch

Media Characteristics

Media Type

Receipt and Label, Linerless (optional)

Media Width

80 mm

Media Roll Diameter

Up to 50 mm

Media Thickness

0.07 ± 0.003 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x D)

110.0 x 162.0 x 58.3 mm

(4.33 x 6.38 x 2.30 inch)

Weight

Including battery: 550 g (1.21 lbs.)

Including MSR: 565 g (1.25 lbs.)

Paper : 133 g (0.29 lbs.)

Battery

7.4 V Li-ion, 2,600 mAh, Rechargeable

Charging time: Up to 4.0 hrs

Performance Characteristics

Memory

64 Mbit SDRAM, 32 Mbit FlashROM

Interface

USB V1.1 FS

Serial

Bluetooth V3.0 + EDR

WLAN 802.11 b/g - WEP40/104, WPA1/2 (PSK, EAP)

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)

Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP54 (with protective case)

Drop Spec

1.5 m (5ft.)

Software

Emulation

BXL / POS

Driver

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver

SDK

iOS SDK, Android SDK, Windows SDK,

Symbian SDK

Fonts/Graphics/Symbologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN: 24 x 24

Characters Per Line

Font A: 48 Font B, C: 64

KOR, CHN: 24

Character Sets

Alphanumeric: 95

Expanded Graphics: 128 x 33 page

International: 32

Graphics

Supporting user-defined fonts, graphics, formats, layouts, and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, MaxiCode, PDF417, QR code

Accessories

Standard

Belt Strap, Battery Pack, Battery Charger,

Power Cord, Paper

Optional

Case, Protective Case, Shoulder Strap,

Single Battery Cradle, Quad Battery Charger,

Vehicle Charger, Serial/USB Cable, Cleaning Pen

Integrated Card Reader (optional)

MSR

3 Track, DUKPT (optional), T-DES Certified (optional)

BR-SPP-R300-EN-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.



BIXOLON®

www.bixolon.com

**BIXOLON Co., Ltd.**

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de