

Description




- LED spotlight with motion detector
- 2 LED spots with 8 W each (equivalent to 2x100 W Halogen spotlight)
- Spotlight can be swivelled $\pm 40^\circ$ horizontally, and adjusted 90° downwards
- Suitable for outdoor use
- Automatic lighting control based on presence and brightness
- 90° detection angle at a detection range of 10 m
- Additional creep under protection with 140° detection angle at a detection range of 2 m
- Sensor head can be turned by $\pm 90^\circ$ horizontally
- Spotlight can be swivelled $\pm 40^\circ$ horizontally, and adjusted 90° downwards
- Area limit via lens attachment
- Single-handed plug-in installation
- Instant start-up possible via factory preset
- Adjustable lux value and switch-off delay
- Settings can be changed without tools
- Optional purely twilight-dependent control
- Not suitable for dimming applications

Technical data


Operating voltage	100 – 240 V AC
Frequency	50 – 60 Hz
Stand-by consumption	~0,3 W
Light measurement	Mixed light measurement
Installation type	Wall installation
Setting range brightness	5 – 200 lx or just presence dependent
LED output (lighting current)	2x8 W (860 lm)
Colour temperature	6000 K, daylight white
Detection angle	$140^\circ/90^\circ$
Light switch-off delay	5 s-10 min
Ambient temperature	$-20^\circ\text{C} \dots +40^\circ\text{C}$
Protection class	II
Type of protection	IP 44

Connection example




Detection range

Mounting height (A)	Head on to (r)	Diagonally (t)
2,5 m	5 m	10 m



Scale drawings



Accessories

LUXA LED corner angle WH

- Article number: 9070756
 Details ► www.theben.de

